

INDUSTRIAL COMPONENT DATA

D150-CI44-RAL7032 098474 2502359 EATON ELECTRIC Covers, RAL7032, HxWxD 375x375x50mm

Brand: EATON - MOELLER | Manufacturer Part Number: D150-CI44-RAL7032



Manufacturer	EATON - MOELLER
MPN / Reference	D150-CI44-RAL7032
Catalog number	2502359
Category	Top-/floor cover element (enclosure/switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-13D9034D48
Generated	2026-08-06

Product Overview

Covers, RAL7032, HxWxD=375x375x50mm

Non-transparent cover, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, sealable cover fasteners, continuous foamed gasket, RAL 7032, mounting depth with mounting plate=150mm, can be used for CI bases E, X and V, lock mechanism type: actuation with tools (not accessible to unqualified personnel)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Insulating Enclosures
--------------	---

Additional Product Information

Covers, RAL7032, HxWxD=375x375x50mm Non-transparent cover, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, sealable cover fasteners, continuous foamed gasket, RAL 7032, mounting depth with mounting plate=150mm, can be used for CI bases E, X and V, lock mechanism type: actuation with tools (not accessible to unqualified personnel) Delivery program

Product range xEnergy Safety Ci Basic function Basic enclosures Product function Enclosure cover Accessories Enclosure cover without apertures Single unit/Complete unit Modular system Standards EN 62208

EN 61439-2 Description Sealable cover fasteners Type cover Non-transparent Colour Non Transparent, RAL 7032, pebble grey Dimensions Width 375 mm Height 375 mm Mounting depth: 150 mm For use with U-CI44... Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV] 18 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Starting enclosure for wall

mounting [PV] 17 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Middle enclosure for wall mounting [PV] 17 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / D150-CI44-RAL7032 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.