

**INDUSTRIAL COMPONENT DATA**

# 40071777000 CrystalWay 19821 1-8h/D IA CGLine+ EATON ELECTRIC CrystalWay 19821 1-8h/D IA CGLine+

Brand: EATON - MOELLER | Manufacturer Part Number: 40071777000



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | 40071777000                        |
| Catalog number  | CrystalWay 19821 1-8h/D IA CGLine+ |
| Category        | Emergency luminaire                |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-72A901F4A8                      |
| Generated       | 2026-08-06                         |

## Product Overview

CrystalWay 19821 1-8h/D IA CGLine+

Eaton CrystalWay, Exit sign, 20m viewing distance, CGLine + technology, LED, Maintained / Non-Maintained operation, IP42, 60lm, 1h/3h/5h/8h selectable duration

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | EATON - MOELLER > Self contained |
|--------------|----------------------------------|

## Additional Product Information

ETIM for 40071777000 Luminaires (EC001957)

Feature Name

Feature Value

Suitable for labelling type (EF001277)

Insert sheet/plate

Type of indicator (EF001278)

Single/double-sided

With pictogram (EF011099)

Yes

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)  
Peripheral (individual battery)  
Battery technology (EF004351)  
Lithium-ions  
Lamp type (EF002423)  
LED non-replaceable  
With light source (EF005905)  
Yes  
Suitable for number of light sources (EF006436)  
1  
Lamp holder (EF000048)  
None  
Number of lighting heads (EF004258)  
24  
Housing material (EF001596)  
Plastic  
Housing colour (EF000136)  
White  
Material cover (EF004284)  
Plastic transparent  
Voltage type (EF000187)  
AC  
Nominal voltage (EF005127)  
230 V  
Type of control gear (EF000381)  
LED driver constant current  
Light distributor (EF012170)  
Diffuser  
Rated life time L70/B50 at 25 °C (EF011870)  
100000 h  
Degree of protection (IP) (EF005474)  
IP42  
Impact strength (EF004293)  
IK04  
Protection class according to IEC 61140 (EF000004)  
II  
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)  
No  
Rated ambient temperature according to IEC 62722-2-1 (EF012090)  
5 °C  
Max. system power (EF009347)  
2.5 W  
Rated luminous flux according to IEC 62722-2-1 (EF009349)  
60 lm  
Luminous flux in standby mode (EF011954)  
3 lm  
Colour temperature (EF009346)

6500 K

Power factor (EF025740)

0.7

Recognition distance (EF008732)

20 m

No...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40071777000 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.