

INDUSTRIAL COMPONENT DATA

CrystalWay 19822 1-8h/D CGLine+ 40071354591 EATON

ELECTRIC CrystalWay 19822 1-8h/D CGLine+

Brand: EATON - MOELLER | Manufacturer Part Number: CrystalWay 19822 1-8h/D CGLine+



Manufacturer	EATON - MOELLER
MPN / Reference	CrystalWay 19822 1-8h/D CGLine+
Catalog number	40071354591
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-1381C08DF8
Generated	2026-08-05

Product Overview

CrystalWay 19822 1-8h/D CGLine+

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Central Battery System

Additional Product Information

ETIM for 40071354591 Luminaires (EC001957)

Feature Name

Feature Value

Suitable for labelling type (EF001277)

Insert sheet/plate

Type of indicator (EF001278)

Single/double-sided

With pictogram (EF011099)

Yes

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)

Battery technology (EF004351)

Lithium-ions

Lamp type (EF002423)

LED non-replaceable

With light source (EF005905)

Yes

Suitable for number of light sources (EF006436)

1

Lamp holder (EF000048)

None

Number of lighting heads (EF004258)

38

Housing material (EF001596)

Plastic

Housing colour (EF000136)

White

Material cover (EF004284)

Plastic transparent

Voltage type (EF000187)

AC

Nominal voltage (EF005127)

230 V

Type of control gear (EF000381)

LED driver constant current

Light distributor (EF012170)

Diffuser

Rated life time L70/B50 at 25 °C (EF011870)

100000 h

Degree of protection (IP) (EF005474)

IP42

Impact strength (EF004293)

IK04

Protection class according to IEC 61140 (EF000004)

II

Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)

No

Rated ambient temperature according to IEC 62722-2-1 (EF012090)

5 °C

Max. system power (EF009347)

4.2 W

Rated luminous flux according to IEC 62722-2-1 (EF009349)

60 lm

Luminous flux in standby mode (EF011954)

3 lm

Colour temperature (EF009346)

6500 K

Power factor (EF025740)

0.7

Recognition distance (EF008732)

30 m

No...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CrystalWay 19822 1-8h/D CGLine+ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.