

INDUSTRIAL COMPONENT DATA

CrystalWay 30m CGLine+ LUM17124 EATON ELECTRIC

CrystalWay 30m CGLine+

Brand: EATON - MOELLER | Manufacturer Part Number: CrystalWay 30m CGLine+



Manufacturer	EATON - MOELLER
MPN / Reference	CrystalWay 30m CGLine+
Catalog number	LUM17124
Category	Emergency luminaire
Minimum order	1 Pcs
Document ID	EO-FB25BA4DD7
Generated	2026-08-04

Product Overview

CrystalWay 30m CGLine+

Eaton CrystalWay 30m Viewing Distance CGLine+

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Central Battery System

Additional Product Information

ETIM for LUM17124 Luminaires (EC001957)

Feature Name

Feature Value

Suitable for labelling type (EF001277)

Insert sheet/plate

Type of indicator (EF001278)

Single/double-sided

With pictogram (EF011099)

Yes

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)
Battery technology (EF004351)
Lithium-ions
Lamp type (EF002423)
LED non-replaceable
With light source (EF005905)
Yes
Suitable for number of light sources (EF006436)
1
Lamp holder (EF000048)
None
Number of lighting heads (EF004258)
38
Housing material (EF001596)
Plastic
Housing colour (EF000136)
White
Material cover (EF004284)
Plastic transparent
Voltage type (EF000187)
AC
Nominal voltage (EF005127)
230 V
Type of control gear (EF000381)
LED driver constant current
Light distributor (EF012170)
Diffuser
Rated life time L70/B50 at 25 °C (EF011870)
100000 h
Degree of protection (IP) (EF005474)
IP42
Impact strength (EF004293)
IK04
Protection class according to IEC 61140 (EF000004)
II
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)
No
Rated ambient temperature according to IEC 62722-2-1 (EF012090)
5 °C
Max. system power (EF009347)
4.2 W
Rated luminous flux according to IEC 62722-2-1 (EF009349)
60 lm
Luminous flux in standby mode (EF011954)
3 lm
Colour temperature (EF009346)
6500 K

Power factor (EF025740)

0.7

Recognition distance (EF008732)

30 m

Nomin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CrystalWay 30m CGLine+ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.