

**INDUSTRIAL COMPONENT DATA**

# CrystalWay 30m CGLine+ LUM17124 EATON ELECTRIC

## CrystalWay 30m CGLine+

Brand: EATON - MOELLER | Manufacturer Part Number: CrystalWay 30m CGLine+



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | EATON - MOELLER        |
| MPN / Reference | CrystalWay 30m CGLine+ |
| Catalog number  | LUM17124               |
| Category        | Emergency luminaire    |
| Minimum order   | 1 Pcs                  |
| Document ID     | EO-FB25BA4DD7          |
| Generated       | 2026-08-06             |

### Product Overview

CrystalWay 30m CGLine+

Eaton CrystalWay 30m Viewing Distance CGLine+

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > Central Battery System**

### Additional Product Information

ETIM for LUM17124 Luminaires (EC001957)

Feature Name

Feature Value

Suitable for labelling type (EF001277)

Insert sheet/plate

Type of indicator (EF001278)

Single/double-sided

With pictogram (EF011099)

Yes

Monitoring equipment (EF008091)

Safety module for monitoring (central feeded system)

With remote switch connection (EF007947)

Yes

Power supply system (EF000233)

Peripheral (individual battery)  
Battery technology (EF004351)  
Lithium-ions  
Lamp type (EF002423)  
LED non-replaceable  
With light source (EF005905)  
Yes  
Suitable for number of light sources (EF006436)  
1  
Lamp holder (EF000048)  
None  
Number of lighting heads (EF004258)  
38  
Housing material (EF001596)  
Plastic  
Housing colour (EF000136)  
White  
Material cover (EF004284)  
Plastic transparent  
Voltage type (EF000187)  
AC  
Nominal voltage (EF005127)  
230 V  
Type of control gear (EF000381)  
LED driver constant current  
Light distributor (EF012170)  
Diffuser  
Rated life time L70/B50 at 25 °C (EF011870)  
100000 h  
Degree of protection (IP) (EF005474)  
IP42  
Impact strength (EF004293)  
IK04  
Protection class according to IEC 61140 (EF000004)  
II  
Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24 (EF006420)  
No  
Rated ambient temperature according to IEC 62722-2-1 (EF012090)  
5 °C  
Max. system power (EF009347)  
4.2 W  
Rated luminous flux according to IEC 62722-2-1 (EF009349)  
60 lm  
Luminous flux in standby mode (EF011954)  
3 lm  
Colour temperature (EF009346)  
6500 K

Power factor (EF025740)

0.7

Recognition distance (EF008732)

30 m

Nomin...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CrystalWay 30m CGLine+ with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.