

INDUSTRIAL COMPONENT DATA

CSAS6A6CY2205 177307 Y7-177307 EATON ELECTRIC

Connection cable 6p AC coupling M12 flat open end L 5m

Brand: EATON - MOELLER | Manufacturer Part Number: CSAS6A6CY2205



Manufacturer	EATON - MOELLER
MPN / Reference	CSAS6A6CY2205
Catalog number	Y7-177307
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-4CBAE492D6
Generated	2026-08-04

Product Overview

Connection cable; 6p; AC; coupling M12 flat; open end; L=5m

CSAS6A6CY2205

Eaton Moeller® series CSAS Connection cable; 6p; AC; coupling M12 flat; open end; L=5m

Connecting cable, Range: connecting cables, Length: 5000 mm, Voltage type: DC, 6 pole, Style output side: Cable end, open, Style input side: Coupling, straight, For use with: RS2...-12..., RS4-12...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series CSAS Accessory Connection cable Catalog Number 177307 Model Code

CSAS6A6CY2205 EAN 4015081717606 Product Length/Depth 250 mm Product Height 25 mm Product Width 175 mm

Product Weight 0.216 kg Compliances CE Product specifications

Number Of Poles Six-pole Cable type Multi-core

Cable end, open, Output side

Coupling, straight, Input side Contact surface material Other Rated operational voltage (Ue) - max 0 V Product category

Accessories Voltage type DC Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C

Continuity resistor 0 m? Nominal current 0 A Cable length 5 m Cable sheath material Other Degree of protection Other

Color cable sheath Yellow Electrical connection type (box-sided) Other Electrical connection type (field-sided) M12 Contact

body material Other Permitted temperature of outer cable (assembled) without vibration - max 70 °C Permitted temperature

of outer cable (assembled) without vibration - min 40 °C Permitted temperature of outer cable (assembling/handling) - max 70 °C Permitted temperature of outer cable (assembling/handling) - min 40 °C Plug-in contact type (field-sided) Female (bus) Positioning cable feed (box-sided) Other Positioning cable feed (field-sided) Straight

ETIM for 177307 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

6

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Female (bu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CSAS6A6CY2205 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.