

INDUSTRIAL COMPONENT DATA

CSAS6A6CY2210 177308 Y7-177308 EATON ELECTRIC

Connection cable 6p AC coupling M12 flat open end L 10m

Brand: EATON - MOELLER | Manufacturer Part Number: CSAS6A6CY2210



Manufacturer	EATON - MOELLER
MPN / Reference	CSAS6A6CY2210
Catalog number	Y7-177308
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-4B340820EF
Generated	2026-08-02

Product Overview

Connection cable; 6p; AC; coupling M12 flat; open end; L=10m

CSAS6A6CY2210

Eaton Moeller® series CSAS Connection cable; 6p; AC; coupling M12 flat; open end; L=10m

Connecting cable, Range: connecting cables, Length: 10000 mm, Voltage type: DC, 6 pole, Style output side: Cable end, open, Style input side: Coupling, straight, For use with: RS2...-12..., RS4-12...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Position Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series CSAS Accessory Connection cable Catalog Number 177308 Model Code

CSAS6A6CY2210 EAN 4015081717613 Product Length/Depth 250 mm Product Height 50 mm Product Width 175 mm

Product Weight 0.442 kg Compliances CE Product specifications

Number Of Poles Six-pole Cable type Coupling, straight, Input side

Cable end, open, Output side

Multi-core Contact surface material Other Rated operational voltage (Ue) - max 0 V Product category Accessories Voltage type DC Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C Continuity resistor 0 m?

Nominal current 0 A Cable length 10 m Cable sheath material Other Degree of protection Other Color cable sheath Yellow

Electrical connection type (box-sided) Other Electrical connection type (field-sided) M12 Contact body material Other

Permitted temperature of outer cable (assembled) without vibration - max 70 °C Permitted temperature of outer cable

(assembled) without vibration - min 40 °C Permitted temperature of outer cable (assembling/handling) - max 70 °C
Permitted temperature of outer cable (assembling/handling) - min 40 °C Plug-in contact type (field-sided) Female (bus)
Positioning cable feed (box-sided) Other Positioning cable feed (field-sided) Straight
ETIM for 177308 Sensors (EC001855)
Feature Name
Feature Value
Number of poles (EF001391)
6
Type of electrical connection, field-sided (EF005525)
M12
Type of plug-in contact, field sided (EF006269)
Female (b...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CSAS6A6CY2210 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.