

INDUSTRIAL COMPONENT DATA

CSDR5A5CY2202 166983 EATON ELECTRIC Connection Cable 5-pole/5-wire DC Connector M12 female right Angle/open ..

Brand: EATON - MOELLER | Manufacturer Part Number: CSDR5A5CY2202



Manufacturer	EATON - MOELLER
MPN / Reference	CSDR5A5CY2202
Catalog number	166983
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-0C1F9EA865
Generated	2026-08-03

Product Overview

Connection Cable; 5-pole/5-wire; DC; Connector M12 female right Angle/open; L=2m

Connection cable, 5p/5Ltg, DC current, coupling m12 angled, open end, 2m

Connecting cable, Basic function: Accessories, Length: 2000 mm, Voltage type: DC, 5 pole, Style output side: Cable end, open, Style input side: Coupling, angled, For use with: DC sensors, IntelliView E75-DST4..., 5 pole, M12

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series CSDR Accessory Connection cable Catalog Number 166983 Model Code CSDR5A5CY2202 EAN 4015081642861 Product Length/Depth 177.8 mm Product Height 25.4 mm Product Width 152.4 mm Product Weight 0.03 kg Compliances CE Product specifications

Type Connecting cables Number Of Poles Five-pole Cable type Multi-core

Coupling, angled, Input side

Cable end, open, Output side Contact surface material Other Rated operational voltage (Ue) - max 0 V Product category

Accessories Voltage type DC Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C

Continuity resistor 0 m? Nominal current 0 A Cable length 2 m Cable sheath material Other Degree of protection Other

Color cable sheath Yellow Electrical connection type (box-sided) Other Electrical connection type (field-sided) M12 Contact

body material Other Permitted temperature of outer cable (assembled) without vibration - max 70 °C Permitted temperature of outer cable (assembled) without vibration - min 40 °C Permitted temperature of outer cable (assembling/handling) - max 70 °C Permitted temperature of outer cable (assembling/handling) - min 40 °C Plug-in contact type (box-sided) Male (plug) Plug-in contact type (field-sided) Female (bus) Positioning cable feed (box-sided) Other Positioning cable feed (field-sided) Angled

ETIM for 166983 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

5

Type of electrical connection, field-sided (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CSDR5A5CY2202 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.