

INDUSTRIAL COMPONENT DATA

CU-BAND5X24X1-BK 119032 Y7-119032 EATON ELECTRIC

Copper band 400A, 5x24x1mm, black

Brand: EATON - MOELLER | Manufacturer Part Number: CU-BAND5X24X1-BK



Manufacturer	EATON - MOELLER
MPN / Reference	CU-BAND5X24X1-BK
Catalog number	Y7-119032
Category	Wiring band
Minimum order	5 Pcs
Document ID	EO-6AD24F65F7
Generated	2026-08-04

Product Overview

Copper band 400A, 5x24x1mm, black

CU-BAND5X24X1-BK

Copper band isolated, laminated conductor E-Cu, tinned, UL approved up to max. 600VAC, insulating material heat resistant up to +105 °C, dimensions (number of layersxwidthxthickness)=5x24x1mm, color black, rated operational current $I_e=400$ A, self-extinguishing according to UL 94 V0, insulation resistance to IEC 60243-1 20 kV/mm, rated operating voltage $U_e=690$ VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Connection Accessories for Enclosures
--------------	---

Additional Product Information

Copper band 400A, 5x24x1mm, blackCopper band isolated, laminated conductor E-Cu, tinned, UL approved up to max. 600VAC, insulating material heat resistant up to +105 °C, dimensions (number of layersxwidthxthickness)=5x24x1mm, color black, rated operational current $I_e=400$ A, self-extinguishing according to UL 94 V0, insulation resistance to IEC 60243-1 20 kV/mm, rated operating voltage $U_e=690$ VAC

General specificationsProduct nameEaton xEffect Multi-Layer Copper Band Enclosures Switch- & Controlgear
EnclosurePart no.CU-BAND5X24X1-BKEAN4015081171590Product Length/Depth2000 millimetreProduct height5 millimetreProduct width24 millimetreProduct weight2.3 kilogramCompliancesEN 60439-1

UL 758

UL CSA09 (max. 105 °C)

CE marking

EN 60439-3

RoHS conformCertificationsUL (Category Control Number AVLV2)

North America (UL listed, certified by UL for use in Canada)

UL (File No. E248096)Product TradenamexEffect Multi-Layer Copper BandProduct TypeEnclosuresProduct Sub TypeSwitch- & Controlgear EnclosureDelivery programTypeGeneral switchboard accessoryAccessory/spare part typeCopper band insulatedColorBlack, similar to RAL 9005Amperage rating400 ATechnical Data - ElectricalVoltage rating1000 V AC, 1500 V DCVoltage rating (UL CSA 13)Max. 600 V AC, 750 V DCRated operation current (Ie)400 ADielectric strength20 kV/mmTechnical Data - MechanicalCross section120 mm²Number of fuse holders (knife blade)5Busbar thickness9 mmDimensions - band specification5 mm x 24 mm x 1 mmLamella thickness1 mmAdditiona...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CU-BAND5X24X1-BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.