

INDUSTRIAL COMPONENT DATA

CUBEFUSE, TCF 100A IND TCF100 EATON ELECTRIC cartridge fuse, BT, 100 A, AC 600 V, DC 300 V, 26 x 32 x 77 mm,..

Brand: EATON - MOELLER | Manufacturer Part Number: TIME DELAY CUBEFUSE 100A IND



Manufacturer	EATON - MOELLER
MPN / Reference	TIME DELAY CUBEFUSE 100A IND
Catalog number	TCF100
Category	Low Voltage HRC fuse
Minimum order	6 Pcs
Document ID	EO-09D7B6DBE3
Generated	2026-08-06

Product Overview

cartridge fuse, BT, 100 A, AC 600 V, DC 300 V, 26 x 32 x 77 mm, CF, J, 1F, UL, CSA, delayed

CUBEFUSE, TCF 100A IND

CUBEFUSE, TCF 100A IND - Fuse-link, low voltage, 100 A, AC 600 V, DC 300 V, 300 kA, 26 x 32 x 77 mm, CF, J, 1P, UL, CSA, finger-safe, time-delay

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, low voltage, 100 A, AC 600 V, DC 300 V, 300 kA, 26 x 32 x 77 mm, CF, J, 1P, UL, CSA, finger-safe, time-delay
Fuse, Fuse-link, low voltage, 100 A, AC 600 V, DC 300 V, 26 x 32 x 77 mm, CF, J, 1P, UL, CSA, time-delay, finger-safe, Breaking Capacity 300 kA, time-delay 10 seconds (minimum) at 500% of rated current
Delivery program
Product range
FuseBasic function
Fuse-linkField of applicationlow voltageRated current [I]_N100 ARated voltageAC 600 V DC 300 VSize26 x 32 x 77 mmUtilization categoryCF
JDescriptionfinger-safeBreaking Capacity300 kANumber of poles1Pusable for size/applicationsElectrical panelboards, industrial control, machinery disconnects, required finger safe systemsRelease characteristic
[class]time-delayStandard/ApprovalUL
CSAStandards/RegulationsUL Listed
CSA CertifiedTime delaytime-delay 10 seconds (minimum) at 500% of rated currentTechnical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 100 A Rated voltage 600 V Voltage type AC/DC Rated switching capacity 300 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TIME DELAY CUBE FUSE 100A IND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.