

INDUSTRIAL COMPONENT DATA

CUBEFUSE, TCF 20A IND TCF20 EATON ELECTRIC Fuse-link, low voltage, 6 A, AC 600 V, DC 300 V, 20 x 26 x 48 mm,..

Brand: EATON - MOELLER | Manufacturer Part Number: TIME DELAY CUBEFUSE 20A IND



Manufacturer	EATON - MOELLER
MPN / Reference	TIME DELAY CUBEFUSE 20A IND
Catalog number	TCF20
Category	Low Voltage HRC fuse
Minimum order	12 Pcs
Document ID	EO-6CE3FCB668
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 6 A, AC 600 V, DC 300 V, 20 x 26 x 48 mm, CF, J, 1P, UL, CSA, time-delay, non-indicating CUBEFUSE, TCF 20A IND

CUBEFUSE, TCF 20A IND - Fuse-link, low voltage, 20 A, AC 600 V, DC 300 V, 300 kA, 20 x 26 x 48 mm, CF, J, 1P, UL, CSA, finger-safe, time-delay

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, low voltage, 20 A, AC 600 V, DC 300 V, 300 kA, 20 x 26 x 48 mm, CF, J, 1P, UL, CSA, finger-safe, time-delay
Fuse, Fuse-link, low voltage, 20 A, AC 600 V, DC 300 V, 20 x 26 x 48 mm, CF, J, 1P, UL, CSA, time-delay, finger-safe, Breaking Capacity 300 kA, time-delay 10 seconds (minimum) at 500% of rated current
Delivery program
Product range
FuseBasic function
Fuse-linkField of applicationlow voltageRated current [I]_n20 ARated voltageAC 600 V DC 300 VSize20 x 26 x 48 mmUtilization categoryCF
JDescriptionfinger-safeBreaking Capacity300 kANumber of poles1Pusable for size/applicationsElectrical panelboards, industrial control, machinery disconnects, required finger safe systemsRelease characteristic
[class]time-delayStandard/ApprovalUL
CSAStandards/RegulationsUL Listed
CSA CertifiedTime delaytime-delay 10 seconds (minimum) at 500% of rated currentTechnical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current20 ARated voltage600 VVoltage typeAC/DCRated switching capacity300 kAUtilization categoryOtherType of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TIME DELAY CUBE FUSE 20A IND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.