

INDUSTRIAL COMPONENT DATA

CUBEFUSE, TCF 3A NON-IND TCF3RN EATON ELECTRIC

Fuse-link, low voltage, 6 A, AC 600 V, DC 300 V, 20 x 26 x 48..

Brand: EATON - MOELLER | Manufacturer Part Number: TIME DELAY CUBEFUSE 3A NON-IND



Manufacturer	EATON - MOELLER
MPN / Reference	TIME DELAY CUBEFUSE 3A NON-IND
Catalog number	TCF3RN
Category	Low Voltage HRC fuse
Minimum order	12 Pcs
Document ID	EO-F5696028C0
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 6 A, AC 600 V, DC 300 V, 20 x 26 x 48 mm, CF, J, 1P, UL, CSA, time-delay, non-indicating
CUBEFUSE, TCF 3A NON-IND

CUBEFUSE, TCF 3A NON-IND - Fuse-link, low voltage, 3 A, AC 600 V, DC 300 V, 300 kA, 20 x 26 x 48 mm, CF, J, 1P, UL, CSA, non-indicating, finger-safe, time-delay

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, low voltage, 3 A, AC 600 V, DC 300 V, 300 kA, 20 x 26 x 48 mm, CF, J, 1P, UL, CSA, non-indicating, finger-safe, time-delay
Fuse, Fuse-link, low voltage, 3 A, AC 600 V, DC 300 V, 20 x 26 x 48 mm, CF, J, 1P, UL, CSA, time-delay, non-indicating, finger-safe, Breaking Capacity 300 kA, time-delay 10 seconds (minimum) at 500% of rated current
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application low voltage
Rated current [I]_N 3 A
Rated voltage AC 600 V
DC 300 V
Size 20 x 26 x 48 mm
Utilization category CF

J Status indicator non-indicating
Description finger-safe
Breaking Capacity 300 kA
Number of poles 1P
Usable for size/applications Electrical panelboards, industrial control, machinery disconnects, required finger safe systems
Release characteristic [class] time-delay
Standard/Approval UL

CSA Standards/Regulations UL Listed

CSA Certified Time delay time-delay 10 seconds (minimum) at 500% of rated current
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current3 ARated voltage600 VVoltage typeAC/DCRated switching capacity300
kAUtilization categoryOtherType of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TIME DELAY CUBE FUSE 3A NON-IND with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.