

## INDUSTRIAL COMPONENT DATA

# CUBEFUSE, TCF 35A NON-IND TCF35RN EATON ELECTRIC

## Fuse-link, low voltage, 6 A, AC 600 V, DC 300 V, 20 x 26 x ..

Brand: EATON - MOELLER | Manufacturer Part Number: CUBEFUSE, TCF 35A NON-IND



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | EATON - MOELLER           |
| MPN / Reference | CUBEFUSE, TCF 35A NON-IND |
| Catalog number  | TCF35RN                   |
| Category        | Low Voltage HRC fuse      |
| Minimum order   | 12 Pcs                    |
| Document ID     | EO-47225105C1             |
| Generated       | 2026-08-06                |

### Product Overview

Fuse-link, low voltage, 6 A, AC 600 V, DC 300 V, 20 x 26 x 48 mm, CF, J, 1P, UL, CSA, time-delay, non-indicating  
CUBEFUSE, TCF 35A NON-IND

CUBEFUSE, TCF 35A NON-IND - Fuse-link, low voltage, 35 A, AC 600 V, DC 300 V, 300 kA, 26 x 29 x 55 mm, CF, J, 1P, UL, CSA, non-indicating, finger-safe, time-delay

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                    |
|--------------|----------------------------------------------------|
| Catalog path | EATON - MOELLER > Bussmann Series High speed fuses |
|--------------|----------------------------------------------------|

### Additional Product Information

Fuse-link, low voltage, 35 A, AC 600 V, DC 300 V, 300 kA, 26 x 29 x 55 mm, CF, J, 1P, UL, CSA, non-indicating, finger-safe, time-delay  
Fuse, Fuse-link, low voltage, 35 A, AC 600 V, DC 300 V, 26 x 29 x 55 mm, CF, J, 1P, UL, CSA, time-delay, non-indicating, finger-safe, Breaking Capacity 300 kA, time-delay 10 seconds (minimum) at 500% of rated current  
Delivery program

Product rangeFuseBasic functionFuse-linkField of applicationlow voltageRated current [I]<sub>N</sub>35 ARated voltageAC 600 V  
DC 300 VSize26 x 29 x 55 mmUtilization categoryCF

JStatus indicatornon-indicatingDescriptionfinger-safeBreaking Capacity300 kANumber of poles1Pusable for  
size/applicationsElectrical panelboards, industrial control, machinery disconnects, required finger safe systemsRelease  
characteristic [class]time-delayStandard/ApprovalUL

CSAStandards/RegulationsUL Listed

CSA CertifiedTime delaytime-delay 10 seconds (minimum) at 500% of rated currentTechnical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected]  
[AFZ800015])Construction sizeOtherRated current35 ARated voltage600 VVoltage typeAC/DCRated switching capacity300  
kAUtilization categoryOtherType of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CUBEFUSE, TCF 35A NON-IND with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.