

## INDUSTRIAL COMPONENT DATA

**CUBEFUSE, TCF 70A IND TCF70 EATON ELECTRIC cartridge fuse, BT, 70 A, AC 600 V, DC 300 V, 26 x 32 x 77 mm, CF..**

Brand: EATON - MOELLER | Manufacturer Part Number: TIME DELAY CUBEFUSE 70A IND



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | EATON - MOELLER             |
| MPN / Reference | TIME DELAY CUBEFUSE 70A IND |
| Catalog number  | TCF70                       |
| Category        | Low Voltage HRC fuse        |
| Minimum order   | 6 Pcs                       |
| Document ID     | EO-B6082EA641               |
| Generated       | 2026-08-06                  |

**Product Overview**

cartridge fuse, BT, 70 A, AC 600 V, DC 300 V, 26 x 32 x 77 mm, CF, J, 1F, UL, CSA, delayed

CUBEFUSE, TCF 70A IND

CUBEFUSE, TCF 70A IND - Fuse-link, low voltage, 70 A, AC 600 V, DC 300 V, 300 kA, 26 x 32 x 77 mm, CF, J, 1P, UL, CSA, finger-safe, time-delay

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                                                    |
|--------------|----------------------------------------------------|
| Catalog path | EATON - MOELLER > Bussmann Series High speed fuses |
|--------------|----------------------------------------------------|

**Additional Product Information**

Fuse-link, low voltage, 70 A, AC 600 V, DC 300 V, 300 kA, 26 x 32 x 77 mm, CF, J, 1P, UL, CSA, finger-safe, time-delay  
Fuse, Fuse-link, low voltage, 70 A, AC 600 V, DC 300 V, 26 x 32 x 77 mm, CF, J, 1P, UL, CSA, time-delay, finger-safe, Breaking Capacity 300 kA, time-delay 10 seconds (minimum) at 500% of rated current  
Delivery program  
Product range  
FuseBasic function  
Fuse-linkField of applicationlow voltageRated current [I]<sub>n</sub>70 ARated voltageAC 600 V DC 300 VSize26 x 32 x 77 mmUtilization categoryCF  
JDescriptionfinger-safeBreaking Capacity300 kANumber of poles1Pusable for size/applicationsElectrical panelboards, industrial control, machinery disconnects, required finger safe systemsRelease characteristic  
[class]time-delayStandard/ApprovalUL  
CSAStandards/RegulationsUL Listed  
CSA CertifiedTime delaytime-delay 10 seconds (minimum) at 500% of rated currentTechnical data ETIM 7.0  
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected])

[AFZ800015])Construction sizeOtherRated current70 ARated voltage600 VVoltage typeAC/DCRated switching capacity300 kAUtilization categoryOtherType of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / TIME DELAY CUBE FUSE 70A IND with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.