

INDUSTRIAL COMPONENT DATA

EMR4-I15-1-A 106943 EATON ELECTRIC Current monitoring relay, 2 W, 0,3 1,5 A, 1 -5 A, 3 15 A

Brand: EATON - MOELLER | Manufacturer Part Number: EMR4-I15-1-A



Manufacturer	EATON - MOELLER
MPN / Reference	EMR4-I15-1-A
Catalog number	106943
Category	Current monitoring relay
Minimum order	1 Pcs
Document ID	EO-BCF5DC2E88
Generated	2026-08-06

Product Overview

Current monitoring relay, 2 W, 0,3 - 1,5 A, 1 -5 A, 3 - 15 A

Relay monitoring intensity; 2 W; 0; 3-1; 5 A; 1-5 A; 3-15 A

Current monitoring relay, I/I= 0.3 - 1.5 A, 1 - 5 A, 3 - 15 A, 24 - 240 V AC, 50/60 Hz, 24 - 240 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Relay timers (KETR, KEMR, KESR)

Additional Product Information

Current monitoring relay, I/I= 0.3 - 1.5 A, 1 - 5 A, 3 - 15 A, 24 - 240 V AC, 50/60 Hz, 24 - 240 V DC
Current monitoring relay single-phase EMR4-I... 60255-6 according to IEC/EN, 22.5 mm wide, current measuring ranges: 0.3-1.5A, 1-5A, 3-15A, switching hysteresis adjustable from 3-30%, response delay 0.1-30s, monitoring of the upper and lower limit, 24-240VAC/DC
Delivery program

This item will continue to be available for a limited time only and is being replaced by the following item: 184754, EMR6-I15-A-1
Product range EMR Measuring and monitoring relays
Basic function Current monitoring relays
Monitoring of single-phase DC and AC networks

Switching hysteresis adjustable from 3 - 30 %

On delay: None = 0 or adjustable from 0.1 to 30 s

Extension of the measurement range possible with current transformers
Monitoring of OvercurrentUndercurrent
Current measuring range [I~I]=0.3 - 1.5 A

1 - 5 A

3 - 15 A
Contact sequence
Supply voltage 24 - 240 V AC, 50/60 Hz

24 - 240 V DCWidth22.5 mmTechnical data

Technical data in sheet catalogueOther technical data (sheet catalogue)Current monitoring relaysDesign verification as per IEC/EN 61439

Technical data for design verificationRated operational current for specified heat dissipation [In]0 AHeat dissipation per pole, current-dependent [Pvid]0 WEquipment heat dissipation, current-dependent [Pvid]0 WStatic heat dissipation, non-current-dependent [Pvs]2 WHeat dissipation capacity [Pdiss]0 WOperating ambient temperature min.-20 °COperating ambient tempe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / EMR4-I15-1-A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.