


INDUSTRIAL COMPONENT DATA

ZW7-400 045329 Y7-45329 EATON ELECTRIC Current transformer-operated overload relay, 270-400A, 1N/O+1N/C

Brand: EATON - MOELLER | Manufacturer Part Number: ZW7-400



Manufacturer	EATON - MOELLER
MPN / Reference	ZW7-400
Catalog number	Y7-45329
Category	Thermal overload relay
Minimum order	1 Pcs
Document ID	EO-FE788C3023
Generated	2026-08-06

Product Overview

Current transformer-operated overload relay, 270-400A, 1N/O+1N/C

Overload relay driven by 270-400 A current transformer

Current transformer-operated overload relay, Product range: ZW7 current transformer-operated overload relays,

Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Protection with heavy starting duty, Mounting

type: Separate mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C,

Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP00

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Thermal Relays
--------------	----------------------------------

Additional Product Information

Current transformer-operated overload relay, 270-400A, 1N/O+1N/CCurrent transformer-operated overload relay, Product range: ZW7 current transformer-operated overload relays, Description: Test/off button, Reset pushbutton manual/auto, Trip-free release, Protection with heavy starting duty, Mounting type: Separate mounting, Auxiliary contacts N/O = Normally open: 1 N/O, Auxiliary contacts N/C = Normally closed: 1 N/C, Standards: IEC/EN 60947, VDE 0660, UL, CSA, Degree of Protection: IP00

General specificationsProduct nameEaton Moeller® series ZW7 Current transformer-operated overload relayPart no.ZW7-400EAN4015080453291Product Length/Depth162.5 millimetreProduct height97 millimetreProduct width200.5 millimetreProduct weight0.639 kilogramCertificationsVDE 0660

CSA-C22.2 No. 14

UL File No.: E29184

CSA

UL Category Control No.: NKCR

CSA File No.: 012528

IEC/EN 60947

CSA Class No.: 3211-03

UL 508

CE

IEC/EN 60947-4-1

ULProduct TradenameZW7Product TypeCurrent transformer-operated overload relayProduct Sub TypeNoneCatalog NotesRated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified.Features & FunctionsFeaturesTrip-free release
Test/off button
Reset pushbutton manual/auto
Protection with heavy starting dutyGeneral informationAmbient operating temperature - min-25 °CAmbient operating temperature - max50 °CAmbient operating temperature (enclosed) - min25 °CAmbient operating temperature (enclosed) - max40 °CClassOtherClimatic proofingDamp....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / ZW7-400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.