

## INDUSTRIAL COMPONENT DATA

# C14M20S EATON ELECTRIC Fuse-link, LV, 20 A, AC 500 V, 14 x 51 mm, aM, IEC, with striker

Brand: EATON - MOELLER | Manufacturer Part Number: C14M20S



|                 |                  |
|-----------------|------------------|
| Manufacturer    | EATON - MOELLER  |
| MPN / Reference | C14M20S          |
| Catalog number  | 10000            |
| Category        | Cylindrical fuse |
| Minimum order   | 10 Pcs           |
| Document ID     | EO-4F2C23E871    |
| Generated       | 2026-08-06       |

## Product Overview

CYL FUSE &gt;STR &gt;14 x 51 20A aM 500V AC

CYL FUSE &gt;STR &gt;14 x 51 20A aM 500V AC

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 20 Amps, 120 kA Breaking capacity, class aM, with striker, compatible with a CH14 Modular fuse holder

Fuse, Fuse-link, low voltage, 20 A, AC 500 V, 14 x 51 mm, aM, IEC, with striker, cylindrical, IEC 60269-2, Breaking Capacity 120 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                     |
|--------------|---------------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories |
|--------------|---------------------------------------------------------------------|

## Additional Product Information

## General specifications

Product Name Eaton Bussmann series low voltage cylindrical fuse Catalog Number C14M20S Model Code CYL FUSE >STR >14 x 51 20A GG 500V AC EAN 5027590494809 Product Length/Depth 51 mm Product Height 14 mm Product Width 14 mm Product Weight 20.9 g Compliances CE Marked

RoHS Compliant Certifications IEC 60269 Product specifications

Type fuse Special features Striker Application Amperage Rating 20 A Fitted with: Striker Fuse size 14 x 51 mm Current type AC Breaking capacity 120 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Rated voltage AC 500 V Class Class aM Fuse type C14M Utilization category aM (switchgear protection) Fuse indicator Top fuse status indicator Watt losses 1.23 W Connection Ferrule end x ferrule end Construction size 14 mm x 51 mm Fuse shape Cylindrical Voltage type AC Suitable for CH14 Modular fuse holder Material Ceramic Mounting method 14 x 51 mm CH Modular fuse holder

Packaging type Standard Release characteristic Other Quantity 10 Voltage rating 500 V

ETIM for C14M20S Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Model (EF000010)

Ceramic fuse

Size (EF000088)

14x51 mm

Voltage type (EF000187)

AC

Rated current (EF000227)

20 A

Utilization category according to IEC 60269 (EF002572)

aM (switchgear protection)

Type of fuse status indicator (EF004473)

Top fuse status indicator

Release characteristic (EF000889)

Other

Power loss at rated current (EF012389)

1.23 W

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C14M20S with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.