

INDUSTRIAL COMPONENT DATA

C14M40S EATON ELECTRIC Fuse-link, LV, 40 A, AC 500 V, 14 x 51 mm, aM, IEC, with striker

Brand: EATON - MOELLER | Manufacturer Part Number: C14M40S



Manufacturer	EATON - MOELLER
MPN / Reference	C14M40S
Catalog number	10000
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-F64AE600BF
Generated	2026-08-06

Product Overview

CYL FUSE >STR >14 x 51 40A aM 500V AC

CYL FUSE >STR >14 x 51 40A aM 500V AC

Eaton Bussmann series low voltage 14 x 51 mm cylindrical/ferrule fuse, rated at 500 Volts AC, 40 Amps, 120 kA Breaking capacity, class aM, with striker, compatible with a CH14 Modular fuse holder

Fuse, Fuse-link, low voltage, 40 A, AC 500 V, 14 x 51 mm, aM, IEC, with striker, cylindrical, IEC 60269-2, Breaking Capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage cylindrical fuse Catalog Number C14M40S Model Code CYL FUSE >STR >14 x 51 40A aM 500V AC EAN 5027590494946 UPC 051712666725 Product Length/Depth 51 mm Product Height 14 mm Product Width 14 mm Product Weight 20.9 g Compliances RoHS Compliant

CE Marked Certifications IEC 60269 Electrical data

Amperage Rating 40 A Voltage rating 500 V Voltage type AC Breaking capacity 120 kA Utilization category aM (switchgear protection) Frequency rating - max 62 Hz Compatible fuse holder

Suitable for CH14 Modular fuse holder

ETIM for C14M40S Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Model (EF000010)

Ceramic fuse

Size (EF000088)

14x51 mm

Voltage type (EF000187)

AC

Rated current (EF000227)

40 A

Utilization category according to IEC 60269 (EF002572)

aM (switchgear protection)

Type of fuse status indicator (EF004473)

Top fuse status indicator

Release characteristic (EF000889)

Other

Power loss at rated current (EF012389)

2.6 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C14M40S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.