

INDUSTRIAL COMPONENT DATA

C22G40S EATON ELECTRIC Fuse-link, LV, 40 A, AC 690 V, 22 x 58 mm, gL/gG, IEC, with striker

Brand: EATON - MOELLER | Manufacturer Part Number: C22G40S



Manufacturer	EATON - MOELLER
MPN / Reference	C22G40S
Catalog number	10000
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-B8602E0AAB
Generated	2026-08-06

Product Overview

CYL FUSE >STR >22 x 58 40A GG 690V AC

40A 690V gL/gG LV Fuse Link with Striker

Eaton Bussmann series low voltage 22 x 58 mm cylindrical/ferrule fuse, rated at 690 Volts AC, 40 Amps, 80 kA Breaking capacity, class gG/gL, with striker, compatible with a CH22 Modular fuse holder

Fuse, Fuse-link, low voltage, 40 A, AC 690 V, 22 x 58 mm, gL/gG, IEC, with striker, cylindrical, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage cylindrical fuse Catalog Number C22G40S EAN 5027590495455 UPC 051712668491 Product Length/Depth 58 mm Product Height 22 mm Product Width 22 mm Product Weight 51.4 g

Compliances RoHS Compliant

CE Marked Certifications IEC 60269 Electrical data

Amperage Rating 40 A Voltage rating 690 V Voltage type AC Breaking capacity 80 kA Utilization category gG (cable protection/equipment protection) Frequency rating - max 62 Hz Compatible fuse holder

Suitable for CH22 Modular fuse holder

ETIM for C22G40S Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Model (EF000010)

Ceramic fuse

Size (EF000088)

22x58 mm

Voltage type (EF000187)

AC

Rated current (EF000227)

40 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Type of fuse status indicator (EF004473)

Top fuse status indicator

Release characteristic (EF000889)

Other

Power loss at rated current (EF012389)

4 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / C22G40S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.