

INDUSTRIAL COMPONENT DATA

D02-LTS/63/3-R 114316 Y7-114316 EATON ELECTRIC

D02-LTS/63/3-R

Brand: EATON - MOELLER | Manufacturer Part Number: D02-LTS/63/3-R



Manufacturer	EATON - MOELLER
MPN / Reference	D02-LTS/63/3-R
Catalog number	Y7-114316
Category	D0-system switch disconnecter
Minimum order	1 Pcs
Document ID	EO-949EE23A6F
Generated	2026-08-05

Product Overview

D02-LTS/63/3-R

Eaton xEffect SASY 60i Enclosures Switch- & Controlgear Enclosure. Bus-mounted switch-disconnector with fuses, 63A, 400 V, 3p, D02

The flash function indicates the blowing of fuse link, delivery empty, without adapter sleeves and fuse links, retaining springs for D01 fuse links or cylindrical fuse links 10x38 supplied, contact position indicator, fuse plug without screw cap, switches the load on all poles and without touching by hand, version D02-LTS/63/3-R-HK with integrated auxiliary contact, sealable and lockable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect SASY 60i busbar system device D02 Catalog Number 114316 Model Code D02-LTS/63/3-R EAN 4015081137169 Product Length/Depth 226 mm Product Height 102 mm Product Width 27 mm Product Weight 0.361 kg Compliances RoHS conform Certifications IEC/EN 60947-3 Delivery program

Type Amperage Rating 63 A Number of poles Three-pole Technical data - electrical

Voltage rating 400 V AC Rated operational voltage (Ue) - max 400 V Rated impulse withstand voltage (Uimp) 6 kV Rated operation current (Ie) 63 A Rated conditional short-circuit current tested with links 63 kA Conventional thermal current Ith of auxiliary contacts (1-pole, open) 63 A Current heat loss per contact at Ie 1.5 W Frequency rating 40 Hz - 60 Hz Frequency rating of contacts 40 Hz - 60 Hz Utilization category AC-22 B Overvoltage category IV Pollution degree 3 Technical data -

mechanical

Enclosure width 226 mm Frame E18, D02, C10x38 Mounting method Busbar with 60 mm clearance Mounting position Vertical or horizontal Mounting width 27 mm per pole (1.5 space units) Degree of protection IP20 enclosed Distance between busbar centers 60 mm Terminals Lift terminals Terminal capacity (solid cable) 1.5 mm² - 35 mm² at box terminal Construction size D02 Thread type E18 Climatic proofing Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 Design verification as per IEC/EN 61439 - technical data Heat dissipation per contact with fuse link at Ie 7 W Permitted heat lo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / D02-LTS/63/3-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.