

INDUSTRIAL COMPONENT DATA

D02-LTS/63/3N-R 114317 Y7-114317 EATON ELECTRIC

D02-LTS/63/3N-R

Brand: EATON - MOELLER | Manufacturer Part Number: D02-LTS/63/3N-R



Manufacturer	EATON - MOELLER
MPN / Reference	D02-LTS/63/3N-R
Catalog number	Y7-114317
Category	D0-system switch disconnecter
Minimum order	1 Pcs
Document ID	EO-995680A91E
Generated	2026-08-06

Product Overview

D02-LTS/63/3N-R

Fuse switch disconnecter, 3pole+N, 63A

Bus-mounted switch-disconnector with fuses, the flash function indicates the blowing of fuse link, delivery empty, without adapter sleeves and fuse links, retaining springs for D01 fuse links or cylindrical fuse links 10 x 38 supplied, contact position indicator, fuse plug without screw cap, switches the load on all poles and without touching by hand, version D02-LTS/63/3-R-HK with integrated auxiliary contact, sealable and lockable, type conforms to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog pathEATON - MOELLER > Connection Accessories for Enclosures

Additional Product Information

Fuse switch disconnecter, 3pole+N, 63A Bus-mounted switch-disconnector with fuses, the flash function indicates the blowing of fuse link, delivery empty, without adapter sleeves and fuse links, retaining springs for D01 fuse links or cylindrical fuse links 10 x 38 supplied, contact position indicator, fuse plug without screw cap, switches the load on all poles and without touching by hand, version D02-LTS/63/3-R-HK with integrated auxiliary contact, sealable and lockable, type conforms to IEC/EN 60947-3

General specificationsProduct nameEaton xEffect SASY 60i busbar system device D02Part

no.D02-LTS/63/3N-REAN4015081137176Product Length/Depth262 millimetreProduct height102 millimetreProduct width27 millimetreProduct weight0.4 kilogramCompliancesRoHS conformCertificationsIEC/EN 60947-3Product TradenamexEffect SASY 60iProduct TypeBusbar system deviceProduct Sub TypeD02Delivery programType185 mm system 60 mm systemNumber of polesFour-poleTechnical Data - ElectricalVoltage rating400 V ACRated operational voltage (Ue) -

max400 VRated impulse withstand voltage (Uimp)6 kVCurrent heat loss per contact at $I_e1.5 W$ Rated operation current (I_e)63 ARated conditional short-circuit current tested with links63 kAFrequency rating40 Hz - 60 HzFrequency rating of contacts40 Hz - 60 HzOvervoltage categoryIVPollution degree3Technical Data - MechanicalEnclosure width226 mmFrameE18, D02, C10x38Mounting methodBusbar with 60 mm clearanceMounting positionVertical or horizontalMounting width27 mm per pol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / D02-LTS/63/3N-R with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.