

INDUSTRIAL COMPONENT DATA

D250-CI48/T-NA 012863 EATON ELECTRIC Covers, +door, transparent, HxWxD 375x750x191mm, NA type

Brand: EATON - MOELLER | Manufacturer Part Number: D250-CI48/T-NA



Manufacturer	EATON - MOELLER
MPN / Reference	D250-CI48/T-NA
Catalog number	012863
Category	Top-/floor cover element (enclosure/switchgear cabinet)
Minimum order	1 Pcs
Document ID	EO-C1D859CE07
Generated	2026-08-06

Product Overview

Covers, +door, transparent, HxWxD=375x750x191mm, NA type

Transparent cover with door, UL approved, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, sealable cover fasteners, continuous foamed gasket, mounting depth with mounting plate=250mm, can be used for CI bases E, X and V, door lock mechanism type: manual operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Insulating Enclosures

Additional Product Information

Covers, +door, transparent, HxWxD=375x750x191mm, NA typeTransparent cover with door, UL approved, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, sealable cover fasteners, continuous foamed gasket, mounting depth with mounting plate=250mm, can be used for CI bases E, X and V, door lock mechanism type: manual operationDelivery program

Product rangexEnergy Safety CiBasic functionBasic enclosuresProduct functionEnclosure covers for North AmericaAccessoriesEnclosure cover with doorSingle unit/Complete unitModular systemStandardsUL508AProtection typeIP65Type coverTransparent, smoky grayMounting depth:250 mmFor use withU-CI48...Design verification as per IEC/EN 61439

Technical data for design verificationHeat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV]40 WHeat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Starting enclosure for wall mounting [PV]38 WHeat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure,

calculated as per IEC 60890 Middle enclosure for wall mounting [PV]35 WHeat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure for wall mounting [PV]80 WHeat dissipation, at an ambient temperature of 35°C, delta T: 35...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / D250-CI48/T-NA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.