

INDUSTRIAL COMPONENT DATA

DA1-35034NB-B55C 176967 Y7-176967 EATON ELECTRIC
Variable frequency drive, 500 V AC, 3-phase, 34 A, 22 kW, I..

Brand: EATON - MOELLER | Manufacturer Part Number: DA1-35034NB-B55C



Manufacturer	EATON - MOELLER
MPN / Reference	DA1-35034NB-B55C
Catalog number	Y7-176967
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-7CD782674C
Generated	2026-08-05

Product Overview

Variable frequency drive, 500 V AC, 3-phase, 34 A, 22 kW, IP55/NEMA 12, OLED display

DA1-35034NB-B55C

Variable frequency drive, Part group reference (e.g. DIL): DA1, Rated operational voltage: $U_e = 500$ V AC, 3-phase, 600 V AC, 3-phase, Output voltage with V_e : $U_2 = 500$ V AC, 3-phase, 600 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 500$ (-10%) - 600 (+10%) V, Rated operational current At 150% overload: $I_e = 34$ A, Note: Rated operational current at a switching frequency of 8 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 500 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 22$ kW, 150 % Overload: $I_M = 33$ A, Assigned motor rating Note: at 525 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 22$ kW, 150 % Overload: $I_M = 31.4$ A, Assigned motor rating Note: at 550 - 600 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 30$ HP, Assigned motor rating 150 % Overload: $I_M = 32$ A, Degree of Protection: IP55/NEMA 12, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): Ethernet IP, DeviceNet, PROFIBUS, PROFINET, Modbus-TCP, EtherCAT, SmartWire-DT, Fitted with: Brake chopper , OLED display, Addi...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DA1 Variable frequency drive Catalog Number 176967 Model Code DA1-35034NB-B55C EAN

4015081714100 Product Length/Depth 240 mm Product Height 450 mm Product Width 173 mm Product Weight 11.5 kg

Certifications RoHS, ISO 9001

CUL

CE

EAC

IEC/EN 61800-3

UL Category Control No.: NMMS, NMMS7

UL report applies to both US and Canada

IEC/EN61800-5

UL 508C

UL File No.: E172143

DNV

Specification for general requirements: IEC/EN 61800-2

Certified by UL for use in Canada

CSA-C22.2 No. 14

UL

IEC/EN61800-3

Safety: EN 61800-5-1: 2003

RCM

UkrSEPRO Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request. General

Cable length 300 m, unscreened, with motor choke, maximum permissible, Motor feeder

150 m, unscreened, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible, Motor feeder

100 m, screened, maximum permissible, Motor feeder Communication interface DeviceNet, optional

PROFINET, optional

OP-Bus (RS485), built in

Modbus RTU, built in

Modbus-TCP, optional

EtherCAT, optional

Ethernet IP, optional

CANopen®, built in

PROFIBUS, optional

SmartWire-DT, optional Connection to SmartWire-DT In conjunction with DX-NET-SWD1 SmartWire DT module

Yes Degree of protection IP55

NEMA 12 Fitted with: Brake chopper

Additional PCB protection

PC connection

Breaking resistance

Control unit....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DA1-35034NB-B55C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.