

INDUSTRIAL COMPONENT DATA

DA1-35043NB-B55C 176968 Y7-176968 EATON ELECTRIC
Variable frequency drive, 500 V AC, 3-phase, 43 A, 30 kW, I..

Brand: EATON - MOELLER | Manufacturer Part Number: DA1-35043NB-B55C



Manufacturer	EATON - MOELLER
MPN / Reference	DA1-35043NB-B55C
Catalog number	Y7-176968
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-772B906622
Generated	2026-08-05

Product Overview

Variable frequency drive, 500 V AC, 3-phase, 43 A, 30 kW, IP55/NEMA 12, OLED display, DC link choke

DA1-35043NB-B55C

Variable frequency drive, Part group reference (e.g. DIL): DA1, Rated operational voltage: $U_e = 500$ V AC, 3-phase, 600 V AC, 3-phase, Output voltage with V_e : $U_2 = 500$ V AC, 3-phase, 600 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 500$ (-10%) - 600 (+10%) V, Rated operational current At 150% overload: $I_e = 43$ A, Note: Rated operational current at a switching frequency of 8 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 500 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 30$ kW, 150 % Overload: $I_M = 43$ A, Assigned motor rating Note: at 525 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 30$ kW, 150 % Overload: $I_M = 42$ A, Assigned motor rating Note: at 550 - 600 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 40$ HP, Assigned motor rating 150 % Overload: $I_M = 41$ A, Degree of Protection: IP55/NEMA 12, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): Ethernet IP, DeviceNet, PROFIBUS, PROFINET, Modbus-TCP, EtherCAT, SmartWire-DT, Fitted with: Brake chopper , OLED....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DA1 Variable frequency drive Catalog Number 176968 Model Code DA1-35043NB-B55C EAN

4015081714117 Product Length/Depth 270 mm Product Height 540 mm Product Width 235 mm Product Weight 22.5 kg

Certifications CE

IEC/EN61800-3

IEC/EN61800-5

Specification for general requirements: IEC/EN 61800-2

Safety: EN 61800-5-1: 2003

UL File No.: E172143

RCM

UkrSEPRO

UL

EAC

CSA-C22.2 No. 14

CUL

UL report applies to both US and Canada

Certified by UL for use in Canada

RoHS, ISO 9001

UL 508C

IEC/EN 61800-3

DNV

UL Category Control No.: NMMS, NMMS7 Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request. General

Cable length 100 m, screened, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible, Motor feeder

300 m, unscreened, with motor choke, maximum permissible, Motor feeder

150 m, unscreened, maximum permissible, Motor feeder Communication interface Modbus-TCP, optional

EtherCAT, optional

Modbus RTU, built in

SmartWire-DT, optional

PROFINET, optional

OP-Bus (RS485), built in

DeviceNet, optional

CANopen®, built in

Ethernet IP, optional

PROFIBUS, optional Connection to SmartWire-DT In conjunction with DX-NET-SWD1 SmartWire DT module

Yes Degree of protection IP55

NEMA 12 Fitted with: Additional PCB protection

PC connection

IGBT inverter

DC link choke

Internal DC link

OL...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DA1-35043NB-B55C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.