

INDUSTRIAL COMPONENT DATA

DA1-35130NB-B55C 176973 Y7-176973 EATON ELECTRIC

Variable frequency drive, 500 V AC, 3-phase, 130 A, 90 kW, ..

Brand: EATON - MOELLER | Manufacturer Part Number: DA1-35130NB-B55C



Manufacturer	EATON - MOELLER
MPN / Reference	DA1-35130NB-B55C
Catalog number	Y7-176973
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-7EA7FDD158
Generated	2026-08-05

Product Overview

Variable frequency drive, 500 V AC, 3-phase, 130 A, 90 kW, IP55/NEMA 12, OLED display, DC link choke
DA1-35130NB-B55C

Variable frequency drive, Part group reference (e.g. DIL): DA1, Rated operational voltage: $U_e = 500 \text{ V AC}$, 3-phase, 600 V AC, 3-phase, Output voltage with V_e : $U_2 = 500 \text{ V AC}$, 3-phase, 600 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 500 (-10\%) - 600 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 130 \text{ A}$, Note: Rated operational current at an operating frequency of 4 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 500 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 90 \text{ kW}$, 150 % Overload: $I_M = 129 \text{ A}$, Assigned motor rating Note: at 525 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 90 \text{ kW}$, 150 % Overload: $I_M = 123 \text{ A}$, Assigned motor rating Note: at 550 - 600 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 125 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 125 \text{ A}$, Degree of Protection: IP55/NEMA 12, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): Ethernet IP, DeviceNet, PROFIBUS, PROFINET, Modbus-TCP, EtherCAT, SmartWire-DT, Fitted with: Brake chopper....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Power XL Frequency Converters**

Additional Product Information

General specifications

Product Name Eaton DA1 Variable frequency drive Catalog Number 176973 Model Code DA1-35130NB-B55C EAN

4015081714162 Product Length/Depth 313.5 mm Product Height 865 mm Product Width 330 mm Product Weight 50 kg

Certifications UL File No.: E172143

UL Category Control No.: NMMS, NMMS7

EAC

IEC/EN61800-3

CUL

Safety: EN 61800-5-1: 2003

UL

UL 508C

IEC/EN61800-5

UkrSEPRO

CSA-C22.2 No. 14

DNV

UL report applies to both US and Canada

CE

RCM

Certified by UL for use in Canada

Specification for general requirements: IEC/EN 61800-2

RoHS, ISO 9001

IEC/EN 61800-3 Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request. General

Cable length 200 m, screened, with motor choke, maximum permissible, Motor feeder

100 m, screened, maximum permissible, Motor feeder

300 m, unscreened, with motor choke, maximum permissible, Motor feeder

150 m, unscreened, maximum permissible, Motor feeder Communication interface Ethernet IP, optional

SmartWire-DT, optional

PROFINET, optional

DeviceNet, optional

OP-Bus (RS485), built in

EtherCAT, optional

Modbus RTU, built in

CANopen®, built in

Modbus-TCP, optional

PROFIBUS, optional Connection to SmartWire-DT Yes

In conjunction with DX-NET-SWD1 SmartWire DT module Degree of protection NEMA 12

IP55 Fitted with: DC link choke

OLED display

Internal DC link

IGBT inverter

Brake chopper

Breaking resist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DA1-35130NB-B55C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.