

INDUSTRIAL COMPONENT DATA

DA1-356D5NB-B6SC 177015 Y7-177015 EATON ELECTRIC
Variable frequency drive, 500 V AC, 3-phase, 6.5 A, 4 kW, I..

Brand: EATON - MOELLER | Manufacturer Part Number: DA1-356D5NB-B6SC



Manufacturer	EATON - MOELLER
MPN / Reference	DA1-356D5NB-B6SC
Catalog number	Y7-177015
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-18F8486B14
Generated	2026-08-03

Product Overview

Variable frequency drive, 500 V AC, 3-phase, 6.5 A, 4 kW, IP66/NEMA 4X, OLED display, Local controls

DA1-356D5NB-B6SC

Variable frequency drive, Part group reference (e.g. DIL): DA1, Rated operational voltage: $U_e = 500$ V AC, 3-phase, 600 V AC, 3-phase, Output voltage with V_e : $U_2 = 500$ V AC, 3-phase, 600 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 500$ (-10%) - 600 (+10%) V, Rated operational current At 150% overload: $I_e = 6.5$ A, Note: Rated operational current at a switching frequency of 8 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 500 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 4$ kW, 150 % Overload: $I_M = 6.5$ A, Assigned motor rating Note: at 525 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 4$ kW, 150 % Overload: $I_M = 6.5$ A, Assigned motor rating Note: at 550 - 600 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 5$ HP, Assigned motor rating 150 % Overload: $I_M = 6.1$ A, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): Ethernet IP, DeviceNet, PROFIBUS, PROFINET, Modbus-TCP, EtherCAT, Fitted with: Brake chopper, OLED display , Loc...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DA1 Variable frequency drive Catalog Number 177015 Model Code DA1-356D5NB-B6SC EAN

4015081714582 Product Length/Depth 239.3 mm Product Height 257 mm Product Width 188 mm Product Weight 1.8 kg

Certifications UL report applies to both US and Canada

IEC/EN61800-3

RCM

UL 508C

UL Category Control No.: NMMS, NMMS7

Specification for general requirements: IEC/EN 61800-2

RoHS, ISO 9001

CE

CUL

CSA-C22.2 No. 14

IEC/EN 61800-3

IEC/EN61800-5

UL

Certified by UL for use in Canada

UkrSEPRO

UL File No.: E172143

EAC

Safety: EN 61800-5-1: 2003 Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request.

General

Cable length 150 m, unscreened, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible, Motor feeder

100 m, screened, maximum permissible, Motor feeder

300 m, unscreened, with motor choke, maximum permissible, Motor feeder Communication interface CANopen®, built in OP-Bus (RS485), built in

Modbus-TCP, optional

Ethernet IP, optional

EtherCAT, optional

PROFINET, optional

DeviceNet, optional

PROFIBUS, optional

Modbus RTU, built in Connection to SmartWire-DT No Degree of protection IP66

NEMA 4X Fitted with: Brake chopper

Control unit

Additional PCB protection

PC connection

Local controls

OLED display

Internal DC link

Breaking resistance

IGBT inverter Frame size FS2 Funct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DA1-356D5NB-B6SC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.