

## INDUSTRIAL COMPONENT DATA

**DB1-349D5FB-N2CC 197566 Y7-197566 EATON ELECTRIC DB1-349D5FB-N2CC**

Brand: EATON - MOELLER | Manufacturer Part Number: DB1-349D5FB-N2CC



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | DB1-349D5FB-N2CC                   |
| Catalog number  | Y7-197566                          |
| Category        | Frequency converter less than 1 kV |
| Minimum order   | 10 Pcs                             |
| Document ID     | EO-BDE9D12283                      |
| Generated       | 2026-08-04                         |

**Product Overview**

DB1-349D5FB-N2CC

Eaton DB1 Variable frequency drive, 400 V AC, 3-phase, 9.5 A, 4 kW, IP20/NEMA 0, Radio interference suppression filter, FS2

Frequency inverter, Part group reference (e.g. DIL): DB1, Rated operational voltage:  $U_e = 400 \text{ V AC}$ , 3-phase, 480 V AC, 3-phase, Output voltage with  $V_e$ :  $U_2 = 400 \text{ V AC}$ , 3-phase, 480 V AC, 3-phase, Mains voltage (50/60Hz):  $U_{LN} = 380 (-10\%) - 480 (+10\%) \text{ V}$ , Rated operational current At 150% overload:  $I_e = 9.5 \text{ A}$ , Note: Rated operational current at an operating frequency of 8 kHz and an ambient air temperature of  $+60^\circ\text{C}$ , depending on cooling, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload:  $P = 4 \text{ kW}$ , 150 % Overload:  $I_M = 9.5 \text{ A}$ , Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload:  $P = 5 \text{ HP}$ , Assigned motor rating 150 % Overload:  $I_M = 9.5 \text{ A}$ , Degree of Protection: IP20/NEMA 0, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fitted with: Radio interference suppression filter, Frame size: FS2, Standards: General requirements: IEC/EN 61800-2, EMV requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

Catalog path EATON - MOELLER &gt; Power XL Frequency Converters

**Additional Product Information**

General specifications

Product Name Eaton DB1 Variable frequency drive Catalog Number 197566 Model Code DB1-349D5FB-N2CC EAN

4015081943357 Product Length/Depth 89 mm Product Height 193 mm Product Width 140 mm Product Weight 1.15 kg

Certifications UL File No.: E172143

IEC/EN 61800-2

IEC/EN61800-5

Safety: EN 61800-5-1: 2003

CSA-C22.2 No. 14

CUL

UL 508C

UL report applies to both US and Canada

RCM

IEC/EN61800-3

UL Category Control No.: NMMS, NMMS7

Certified by UL for use in Canada

IEC/EN 61800-3

RoHS, ISO 9001

CE

UL

CSA-C22.2 No. 274

IEC/EN 61800-5-1

CE marking Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request. Features & Functions

Features Tool-less swapping of fan

Temperature-controlled fan

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App) Fitted with: Internal DC link

Radio interference suppression filter

IGBT inverter

Breaking resistance

PC connection

Additional PCB protection General

Cable length C1  $\leq$  1 m, maximum motor cable length

C2  $\leq$  3 m, maximum motor cable length

C3  $\leq$  10 m, maximum motor cable length

10 m, screened, maximum permissible cable length Communication interface OP-Bus (RS485)

Modbus RTU

CANopen® Connection to SmartWire-DT No Degree of protection IP20

NEMA Other Electromagnetic compatibility 1st and 2nd environments (accordin...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DB1-349D5FB-N2CC with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.