


## INDUSTRIAL COMPONENT DATA

# DILM150-XSP(RDC60) 230116 Y7-230116 EATON ELECTRIC DC replacement coil for DILM115-150

Brand: EATON - MOELLER | Manufacturer Part Number: DILM150-XSP(RDC60)



|                 |                    |
|-----------------|--------------------|
| Manufacturer    | EATON - MOELLER    |
| MPN / Reference | DILM150-XSP(RDC60) |
| Catalog number  | Y7-230116          |
| Category        | Coil for relay     |
| Minimum order   | 1 Pcs              |
| Document ID     | EO-182207B340      |
| Generated       | 2026-08-05         |

## Product Overview

DC replacement coil for DILM115-150

DILM150-XSP(RDC60)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RDC 60: 48 - 60 V DC, DC, For use with: DILM115, DILM150, DILM170

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RDC 60: 48 - 60 V DC, Voltage AC/DC: DC, For use with: DILM115, DILM150, DILM170, DILM115 - DILM170 (incl. electronic module)

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                         |
|--------------|-----------------------------------------|
| Catalog path | EATON - MOELLER > Contactors up to 170A |
|--------------|-----------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 230116 Model Code DILM150-XSP(RDC60)  
EAN 4015082301163 Product Length/Depth 51 mm Product Height 110 mm Product Width 63.2 mm Product Weight 0.245 kg  
Certifications UL File No.: E29096

CSA File No.: 012528

CSA-C22.2 No. 14-05

UL 508

UL Category Control No.: NLDX

CSA Class No.: 2411-03, 3211-04

UL

CE

CSA

IEC/EN 60947-4-1 General

Accessories Individual coils Product category Accessories Voltage type DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 48 V Rated control supply voltage (Us) at DC - max 60 V Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical impa...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM150-XSP(RDC60) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.