


INDUSTRIAL COMPONENT DATA

DILM150-XSP(RDC240) 230122 Y7-230122 EATON ELECTRIC

DC replacement coil for DILM115-150

Brand: EATON - MOELLER | Manufacturer Part Number: DILM150-XSP(RDC240)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM150-XSP(RDC240)
Catalog number	Y7-230122
Category	Coil for relay
Minimum order	1 Pcs
Document ID	EO-B3A2DA95CE
Generated	2026-08-05

Product Overview

DC replacement coil for DILM115-150

DILM150-XSP(RDC240)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RDC 240: 200 - 240 V DC, DC, For use with: DILM115, DILM150, DILM170

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RDC 240: 200 - 240 V DC, Voltage AC/DC: DC, For use with: DILM115, DILM150, DILM170, DILM115 - DILM170 (incl. electronic module)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 230122 Model Code DILM150-XSP(RDC240)
EAN 4015082301224 Product Length/Depth 51 mm Product Height 110 mm Product Width 63.2 mm Product Weight 0.245 kg
Certifications CSA Class No.: 2411-03, 3211-04

UL 508

CSA File No.: 012528

CSA-C22.2 No. 14-05

IEC/EN 60947-4-1

UL File No.: E29096

CE

CSA

UL Category Control No.: NLDX

UL General

Accessories Individual coils Product category Accessories Voltage type DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 200 V Rated control supply voltage (Us) at DC - max 240 V Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical i...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM150-XSP(RDC240) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.