


## INDUSTRIAL COMPONENT DATA

# DILM32-XSP(RDC130) 281157 Y7-281157 EATON ELECTRIC DC replacement coil for DILM17-32

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XSP(RDC130)



|                 |                    |
|-----------------|--------------------|
| Manufacturer    | EATON - MOELLER    |
| MPN / Reference | DILM32-XSP(RDC130) |
| Catalog number  | Y7-281157          |
| Category        | Coil for relay     |
| Minimum order   | 1 Pcs              |
| Document ID     | EO-34DF56C654      |
| Generated       | 2026-08-02         |

## Product Overview

DC replacement coil for DILM17-32

DILM32-XSP(RDC130)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RDC 130: 110 - 130 V DC, DC, For use with: DILM17, DILM25, DILM32, DILM38

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RDC 130: 110 - 130 V DC, Voltage AC/DC: DC, For use with: DILM17, DILM25, DILM32, DILM38, DILM17 - DILM38

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                         |
|--------------|-----------------------------------------|
| Catalog path | EATON - MOELLER > Contactors up to 170A |
|--------------|-----------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 281157 Model Code DILM32-XSP(RDC130)  
EAN 4015082811570 Product Length/Depth 66 mm Product Height 55 mm Product Width 46 mm Product Weight 0.156 kg  
Certifications UL

UL Category Control No.: NLDX

CE

CSA

IEC/EN 60947-4-1

UL 508

CSA Class No.: 2411-03, 3211-04

CSA File No.: 012528

UL File No.: E29096

CSA-C22.2 No. 14-05 General

Accessories Individual coils Product category Accessories Voltage type DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 110 V Rated control supply voltage (Us) at DC - max 130 V Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical impac...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XSP(RDC130) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.