


INDUSTRIAL COMPONENT DATA

DILM32-XSP(RDC240) 281158 Y7-281158 EATON ELECTRIC DC replacement coil for DILM17-32

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XSP(RDC240)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM32-XSP(RDC240)
Catalog number	Y7-281158
Category	Coil for relay
Minimum order	1 Pcs
Document ID	EO-68EE6EA0F6
Generated	2026-08-04

Product Overview

DC replacement coil for DILM17-32

DILM32-XSP(RDC240)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RDC 240: 200 - 240 V DC, DC, For use with: DILM17, DILM25, DILM32, DILM38

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RDC 240: 200 - 240 V DC, Voltage AC/DC: DC, For use with: DILM17, DILM25, DILM32, DILM38, DILM17 - DILM38

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 281158 Model Code DILM32-XSP(RDC240)
EAN 4015082811587 Product Length/Depth 66 mm Product Height 55 mm Product Width 46 mm Product Weight 0.156 kg
Certifications IEC/EN 60947-4-1

UL 508

UL

CSA-C22.2 No. 14-05

CSA

UL Category Control No.: NLDX

UL File No.: E29096

CSA Class No.: 2411-03, 3211-04

CSA File No.: 012528

CE General

Accessories Individual coils Product category Accessories Voltage type DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 200 V Rated control supply voltage (Us) at DC - max 240 V Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical impac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XSP(RDC240) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.