

INDUSTRIAL COMPONENT DATA

DILM95-XSP(RDC60) 230081 Y7-230081 EATON ELECTRIC DC replacement coil for DILM80-95

Brand: EATON - MOELLER | Manufacturer Part Number: DILM95-XSP(RDC60)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM95-XSP(RDC60)
Catalog number	Y7-230081
Category	Coil for relay
Minimum order	1 Pcs
Document ID	EO-64FE436A3E
Generated	2026-08-04

Product Overview

DC replacement coil for DILM80-95

DILM95-XSP(RDC60)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RDC 60: 48 - 60 V DC, DC, For use with: DILM80, DILM95

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RDC 60: 48 - 60 V DC, Voltage AC/DC: DC, For use with: DILM80, DILM95, DILM80 - DILM170

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 230081 Model Code DILM95-XSP(RDC60)
EAN 4015082300814 Product Length/Depth 51 mm Product Height 110 mm Product Width 63.2 mm Product Weight 0.256 kg
Compliances CE Marked Certifications IEC 60947-4-1

EN 60947-4-1

CSA Std. C22.2 No. 14-05

UL 508

CSA Class No.: 2411-03, 3211-04

UL File No.: E29096

CSA

CSA-C22.2 No. 14-05

CSA File No.: 012528

UL

CE

UL Category Control No.: NLDX

IEC/EN 60947-4-1 General

Accessories Individual coils Product category Accessories Voltage type DC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 48 V Rated control supply voltage (Us) at DC - max 60 V Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.5 Lifting Does not apply,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM95-XSP(RDC60) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.