

INDUSTRIAL COMPONENT DATA

DDC-1000/2/M4/P-G 6098955 Y8-6098955 EATON ELECTRIC DC switch disconnecter, 1000 A, 2 pole, 1 N/O, 1 N/C, wi..

Brand: EATON - MOELLER | Manufacturer Part Number: DDC-1000/2/M4/P-G



Manufacturer	EATON - MOELLER
MPN / Reference	DDC-1000/2/M4/P-G
Catalog number	Y8-6098955
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-B75D943BD7
Generated	2026-08-05

Product Overview

DC switch disconnecter, 1000 A, 2 pole, 1 N/O, 1 N/C, with grey knob, rear mounting

DDC-1000/2/M4/P-G

DC switch disconnecter, Product range: DC switch-disconnector, Main switch, maintenance switch, Part group reference: DDC, with grey knob, Notes: With metal shaft for a control panel depth of 400 mm, Information about equipment supplied: auxiliary contact fitted by user., 2 pole, Degree of Protection: IP20, Design: rear mounting, Rated uninterrupted current: I_u = 1000 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

General specifications

Product Name Eaton DDC Insulated enclosure Catalog Number 6098955 Model Code DDC-1000/2/M4/P-G EAN

8711426214088 Product Length/Depth 345 mm Product Height 160 mm Product Width 230 mm Product Weight 14 kg

Certifications IEC/EN 60204

RoHS

IEC/EN 60947-3

VDE 0660

CE

IEC/EN 60947 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second Features & Functions

Actuator color Gray Actuator type Long turning handle Features Version as maintenance-/service switch

Version as main switch Fitted with: Metal shaft for a control panel depth of 400 mm

Gray knob Functions Interlockable Number of poles Two-pole General

Accessories Auxiliary contact fitted by user. Degree of protection NEMA Other Degree of protection (front side) IP20

Lifespan, mechanical 5,000 Operations Mounting method Rear mounting Mounting position As required Overvoltage

category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 12000 V Suitable for Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 2 x (60 x 5) mm² , Flat conductor connection with busbars Screw size M12 (2 x), Terminal screw

Tightening torque 28 Nm, Screw terminals Electrical rating

Rated operational current (Ie) at DC-21B, 1000 V 1000 A Rated operational current (Ie) at DC-21B, 480....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DDC-1000/2/M4/P-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.