

INDUSTRIAL COMPONENT DATA

DDC-1250/2 6098956 Y8-6098956 EATON ELECTRIC DC switch disconnecter, 1250 A, 2 pole, 1 N/O, 1 N/C, with grey..

Brand: EATON - MOELLER | Manufacturer Part Number: DDC-1250/2



Manufacturer	EATON - MOELLER
MPN / Reference	DDC-1250/2
Catalog number	Y8-6098956
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-3B94D2922F
Generated	2026-08-05

Product Overview

DC switch disconnecter, 1250 A, 2 pole, 1 N/O, 1 N/C, with grey knob, service distribution board mounting
DDC-1250/2

DC switch disconnecter, Product range: DC switch-disconnector, Main switch, maintenance switch, Part group reference: DDC, with grey knob, Information about equipment supplied: auxiliary contact fitted by user., 2 pole, Degree of Protection: IP20, Design: service distribution board mounting, Rated uninterrupted current: I_u = 1250 A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DDC Insulated enclosure Catalog Number 6098956 Model Code DDC-1250/2 EAN 8711426212800
Product Length/Depth 345 mm Product Height 160 mm Product Width 230 mm Product Weight 14 kg Certifications CE
IEC/EN 60947

RoHS

IEC/EN 60947-3

VDE 0660

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second Features & Functions

Actuator color Gray Actuator type Long turning handle Features Version as main switch

Version as maintenance-/service switch Fitted with: Gray knob Functions Interlockable Number of poles Two-pole General

Accessories Auxiliary contact fitted by user. Degree of protection NEMA Other Degree of protection (front side) IP20
Lifespan, mechanical 5,000 Operations Mounting method Service distribution board mounting Mounting position As required
Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 12000 V Suitable for
Ground mounting Climatic environmental conditions
Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min
-30 °C Ambient storage temperature - max 80 °C Terminal capacities
Terminal capacity 2 x (80 x 5) mm² , Flat conductor connection with busbars Screw size M12 (2 x), Terminal screw
Tightening torque 28 Nm, Screw terminals Electrical rating
Rated operational current (Ie) at DC-21B, 1000 V 1250 A Rated operational current (Ie) at DC-21B, 480 V 1250 A Rated
operational curren...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DDC-1250/2 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.