

INDUSTRIAL COMPONENT DATA

DC1-12011NB-A20CE1 185797 Y7-185797 EATON ELECTRIC
Variable frequency drive, 230 V AC, 1-phase, 10.5 A, 2.2 ..

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-12011NB-A20CE1



Manufacturer	EATON - MOELLER
MPN / Reference	DC1-12011NB-A20CE1
Catalog number	Y7-185797
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-D6013A062C
Generated	2026-08-05

Product Overview

Variable frequency drive, 230 V AC, 1-phase, 10.5 A, 2.2 kW, IP20/NEMA 0, Brake chopper, FS2

DC1-12011NB-A20CE1

Eaton DC1 Variable frequency drive, 230 V AC, 1-phase, 10.5 A, 2.2 kW, IP20/NEMA 0, Brake chopper, FS2

DC1-12011NB-A20CE1

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 230 \text{ V AC}$, 1-phase, 240 V AC, single-phase, Output voltage with V_e : $U_2 = 230 \text{ V AC}$, 3-phase, 240 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 200 (-10\%) - 240 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 10.5 \text{ A}$, Note: Rated operational current at an operating frequency of 16 kHz and an ambient air temperature of $+50^\circ\text{C}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 230 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 2.2 \text{ kW}$, 150 % Overload: $I_M = 8.7 \text{ A}$, Assigned motor rating Note: at 220 - 240 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 3 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 9.6 \text{ A}$, Degree of Protection: IP20/NEMA 0, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Brake chopper, 7-digital display assembly, Frame size: FS2, Standards: Specificat...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DC1 Variable frequency drive Catalog Number 185797 Model Code DC1-12011NB-A20CE1 EAN

4015081812967 Product Length/Depth 152 mm Product Height 231 mm Product Width 107 mm Product Weight 2 kg

Certifications CSA-C22.2 No. 14

Specification for general requirements: IEC/EN 61800-2

IEC/EN 61800-3

IEC/EN61800-5

Certified by UL for use in Canada

RCM

CUL

Safety requirements: IEC/EN 61800-5-1

UkrSEPRO

UL

UL 508C

UL Category Control No.: NMMS, NMMS7

UL File No.: E172143

IEC/EN61800-3

RoHS, ISO 9001

CE

EAC

UL report applies to both US and Canada Catalog Notes Features & Functions

Features Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)

Parameterization: Fieldbus

Parameterization: Keypad Fitted with: 7-digital display assembly

IGBT inverter

Brake chopper

PC connection

Breaking resistance

Control unit

Internal DC link

Additional PCB protection Functions 4-quadrant operation possible General

Cable length 300 m, unscreened, with motor choke, maximum permissible, Motor feeder

150 m, unscreened, maximum permissible, Motor feeder

100 m, screened, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible, Motor feeder Communication interface Modbus RTU, built in SmartWire-DT, optional

CANopen®, built in

OP-Bus (RS485), built in Connection to SmartWire-DT In conjunction with DX-NET-SWD3 SmartWire DT module

Yes Degree of protection IP20

NEMA Other Frame size FS2 Mounting position Vertical Product...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-12011NB-A20CE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.