

INDUSTRIAL COMPONENT DATA

**DC1-12015FB-A6SOE1 199410 Y7-199410 EATON ELECTRIC
DC1-12015FB-A6SOE1**

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-12015FB-A6SOE1



Manufacturer	EATON - MOELLER
MPN / Reference	DC1-12015FB-A6SOE1
Catalog number	Y7-199410
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-91DF8B1545
Generated	2026-08-04

Product Overview

DC1-12015FB-A6SOE1

Eaton DC1 Variable frequency drive, 230 V AC, 1-phase, 15.3 A, 4 kW, IP66/NEMA 4X, Radio interference suppression filter, Brake chopper, 7-digital display assembly, Local controls, Additional PCB protection, UV resistant, FS3

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 230 \text{ V AC}$, 1-phase, 240 V AC, single-phase, Output voltage with V_e : $U_2 = 230 \text{ V AC}$, 3-phase, 240 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 200 (-10\%) - 240 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 15.3 \text{ A}$, Note: Rated operational current at an operating frequency of 6 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For normal internally and externally ventilated four-pole three-phase asynchronous motors with 1500 rpm at 50 Hz and 1800 rpm at 60 Hz, Overload cycle for 60 s every 600 s, at 230 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 4 \text{ kW}$, 150 % Overload: $I_M = 14.8 \text{ A}$, Assigned motor rating Note: at 220 - 240 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 5 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 15.2 \text{ A}$, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Radio interference suppression filter, Brake chopper, 7-digital display...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DC1 Variable frequency drive Catalog Number 199410 Model Code DC1-12015FB-A6SOE1 EAN 4015081977994 Product Length/Depth 238 mm Product Height 310 mm Product Width 210.5 mm Product Weight 7 kg

Certifications CUL

UL Listed

UL File No.: E172143

CE

IEC/EN 61800-2

IEC/EN 61800-3

UL report applies to both US and Canada

Certified by UL for use in Canada

RoHS, ISO 9001

UL

UL 508C

CSA-C22.2 No. 14

EAC

CE marking

UkrSEPRO

UL Category Control No.: NMMS, NMMS7

RCM

IEC/EN61800-5

IEC/EN 61800-5-1 Catalog Notes Features & Functions

Features Parameterization: drivesConnect

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: drivesConnect mobile (App) Fitted with: Internal DC link

IGBT inverter

Control unit

7-digital display assembly

Local controls

Breaking resistance

Radio interference suppression filter

PC connection

UV resistance

Additional PCB protection

Brake chopper Functions 4-quadrant operation possible General

Cable length 100 m, screened, maximum permissible cable length

150 m, unscreened, maximum permissible cable length

200 m, screened, with motor choke, maximum permissible cable length

300 m, unscreened, with motor choke, maximum permissible, Motor feeder Communication interface CANopen®, built in

Modbus RTU, built in

OP-Bus (RS485), built in

SmartWire-DT, optional Connection to SmartWire-DT No Degree of protection IP66

NEMA 4X Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Frame size F...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-12015FB-A6SOE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.