

INDUSTRIAL COMPONENT DATA

DC1-124D3NN-A20CE1 185788 Y7-185788 EATON ELECTRIC

Variable frequency drive, 230 V AC, 1-phase, 4.3 A, 0.75 ..

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-124D3NN-A20CE1



Manufacturer	EATON - MOELLER
MPN / Reference	DC1-124D3NN-A20CE1
Catalog number	Y7-185788
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-833C9D13D3
Generated	2026-08-06

Product Overview

Variable frequency drive, 230 V AC, 1-phase, 4.3 A, 0.75 kW, IP20/NEMA 0, FS1

DC1-124D3NN-A20CE1

Eaton DC1 Variable frequency drive, 230 V AC, 1-phase, 4.3 A, 0.75 kW, IP20/NEMA 0, FS1 DC1-124D3NN-A20CE1

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 230 \text{ V AC}$, 1-phase, 240 V AC, single-phase, Output voltage with V_e : $U_2 = 230 \text{ V AC}$, 3-phase, 240 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 200 (-10\%) - 240 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 4.3 \text{ A}$, Note: Rated operational current at an operating frequency of 16 kHz and an ambient air temperature of $+50^\circ\text{C}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 230 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 0.75 \text{ kW}$, 150 % Overload: $I_M = 3.2 \text{ A}$, Assigned motor rating Note: at 220 - 240 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 1 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 4.2 \text{ A}$, Degree of Protection: IP20/NEMA 0, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: 7-digital display assembly, Frame size: FS1, Standards: Specification for general requirements: IEC/EN 61800-2,...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DC1 Variable frequency drive Catalog Number 185788 Model Code DC1-124D3NN-A20CE1 EAN

4015081812875 Product Length/Depth 124 mm Product Height 184 mm Product Width 81 mm Product Weight 1.2 kg

Certifications IEC/EN61800-5

CE

UL

RoHS, ISO 9001

Specification for general requirements: IEC/EN 61800-2

EAC

UL report applies to both US and Canada

UL 508C

IEC/EN 61800-3

UL File No.: E172143

Certified by UL for use in Canada

IEC/EN61800-3

CSA-C22.2 No. 14

Safety requirements: IEC/EN 61800-5-1

UkrSEPRO

RCM

CUL

UL Category Control No.: NMMS, NMMS7 Catalog Notes Features & Functions

Features Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)

Parameterization: Fieldbus

Parameterization: Keypad Fitted with: PC connection

Internal DC link

IGBT inverter

7-digital display assembly

Control unit

Additional PCB protection General

Cable length 100 m, screened, with motor choke, maximum permissible, Motor feeder

75 m, unscreened, maximum permissible, Motor feeder

50 m, screened, maximum permissible, Motor feeder

150 m, unscreened, with motor choke, maximum permissible, Motor feeder Communication interface OP-Bus (RS485), built in

Modbus RTU, built in

CANopen®, built in

SmartWire-DT, optional Connection to SmartWire-DT In conjunction with DX-NET-SWD3 SmartWire DT module

Yes Degree of protection IP20

NEMA Other Frame size FS1 Mounting position Vertical Product category Variable frequency drives Protection Finger and back-of-hand proo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-124D3NN-A20CE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.