

INDUSTRIAL COMPONENT DATA

**DC1-32011FB-A66OE1 199419 Y7-199419 EATON ELECTRIC
DC1-32011FB-A66OE1**

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-32011FB-A66OE1



Manufacturer	EATON - MOELLER
MPN / Reference	DC1-32011FB-A66OE1
Catalog number	Y7-199419
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-17F7C28CAF
Generated	2026-08-05

Product Overview

DC1-32011FB-A66OE1

Eaton DC1 Variable frequency drive, 230 V AC, 3-phase, 10.5 A, 2.2 kW, IP66/NEMA 4X, Radio interference suppression filter, Brake chopper, 7-digital display assembly, Additional PCB protection, UV resistant, FS2

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 230 \text{ V AC}$, 3-phase, 240 V AC, 3-phase, Output voltage with V_e : $U_2 = 230 \text{ V AC}$, 3-phase, 240 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 200 (-10\%) - 240 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 10.5 \text{ A}$, Note: Rated operational current at an operating frequency of 6 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For normal internally and externally ventilated four-pole three-phase asynchronous motors with 1500 rpm at 50 Hz and 1800 rpm at 60 Hz, Overload cycle for 60 s every 600 s, at 230 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 2.2 \text{ kW}$, 150 % Overload: $I_M = 8.7 \text{ A}$, Assigned motor rating Note: at 220 - 240 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 3 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 9.6 \text{ A}$, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Radio interference suppression filter, Brake chopper, 7-digital display assembly, Addition...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DC1 Variable frequency drive Catalog Number 199419 Model Code DC1-32011FB-A66OE1 EAN 4015081978083 Product Length/Depth 182 mm Product Height 257 mm Product Width 188 mm Product Weight 3.5 kg

Certifications UkrSEPRO

RCM

UL File No.: E172143

UL Listed

EAC

IEC/EN 61800-2

IEC/EN61800-5

UL 508C

CE

IEC/EN 61800-5-1

UL report applies to both US and Canada

CUL

IEC/EN 61800-3

RoHS, ISO 9001

Certified by UL for use in Canada

CE marking

UL

CSA-C22.2 No. 14

UL Category Control No.: NMMS, NMMS7 Catalog Notes Features & Functions

Features Parameterization: Fieldbus

Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)

Parameterization: Keypad Fitted with: PC connection

UV resistance

7-digital display assembly

Additional PCB protection

Breaking resistance

Control unit

Internal DC link

IGBT inverter

Brake chopper

Radio interference suppression filter Functions 4-quadrant operation possible General

Cable length 100 m, screened, maximum permissible cable length

200 m, screened, with motor choke, maximum permissible cable length

C2 <= 5 m, maximum motor cable length

300 m, unscreened, with motor choke, maximum permissible, Motor feeder

C3 <= 25 m, maximum motor cable length

150 m, unscreened, maximum permissible cable length Communication interface OP-Bus (RS485), built in

SmartWire-DT, optional

Modbus RTU, built in

CANopen®, built in Connection to SmartWire-DT No Degree of protection NEMA 4X

IP66 Electromagnetic compatibility 1st...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-32011FB-A66OE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.