

INDUSTRIAL COMPONENT DATA

DC1-34014FB-A20CE1 185758 Y7-185758 EATON ELECTRIC

Variable frequency drive, 400 V AC, 3-phase, 14 A, 5.5 kW..

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-34014FB-A20CE1



Manufacturer	EATON - MOELLER
MPN / Reference	DC1-34014FB-A20CE1
Catalog number	Y7-185758
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-77DF8BD62D
Generated	2026-08-04

Product Overview

Variable frequency drive, 400 V AC, 3-phase, 14 A, 5.5 kW, IP20/NEMA 0, Radio interference suppression filter, Brake chopper, FS3

DC1-34014FB-A20CE1

Eaton DC1 Variable frequency drive, 400 V AC, 3-phase, 14 A, 5.5 kW, IP20/NEMA 0, Radio interference suppression filter, Brake chopper, FS3 DC1-34014FB-A20CE1

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-10\%) - 480 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 14 \text{ A}$, Note: Rated operational current at an operating frequency of 16 kHz and an ambient air temperature of $+50^\circ \text{C}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 5.5 \text{ kW}$, 150 % Overload: $I_M = 11.3 \text{ A}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 10 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 14 \text{ A}$, Degree of Protection: IP20/NEMA 0, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Radio interfe...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Power XL Frequency Converters**

Additional Product Information

General specifications

Product Name Eaton DC1 Variable frequency drive Catalog Number 185758 Model Code DC1-34014FB-A20CE1 EAN 4015081812578 Product Length/Depth 175 mm Product Height 273 mm Product Width 129 mm Product Weight 6 kg

Certifications UL 508C

IEC/EN61800-5

UL Category Control No.: NMMS, NMMS7

CSA-C22.2 No. 14

CUL

RCM

EAC

IEC/EN 61800-3

IEC/EN61800-3

UkrSEPRO

RoHS, ISO 9001

Specification for general requirements: IEC/EN 61800-2

UL File No.: E172143

UL report applies to both US and Canada

Safety requirements: IEC/EN 61800-5-1

CE

Certified by UL for use in Canada

UL Catalog Notes Features & Functions

Features Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)

Parameterization: Fieldbus

Parameterization: Keypad Fitted with: 7-digital display assembly

Radio interference suppression filter

IGBT inverter

Breaking resistance

Control unit

Internal DC link

PC connection

Brake chopper

Additional PCB protection Functions 4-quadrant operation possible General

Cable length 150 m, unscreened, maximum permissible, Motor feeder

C2 ≤ 5 m, Radio interference level, maximum motor cable length

300 m, unscreened, with motor choke, maximum permissible, Motor feeder

100 m, screened, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible, Motor feeder

C3 ≤ 25 m, Radio interference level, maximum motor cable length Communication interface SmartWire-DT, optional

OP-Bus (RS485), built in

Modbus RTU, built in

CANopen®, built in Conn...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-34014FB-A20CE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.