

INDUSTRIAL COMPONENT DATA

**DC1-34014FB-A6SOE1 199440 Y7-199440 EATON ELECTRIC
DC1-34014FB-A6SOE1**

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-34014FB-A6SOE1



Manufacturer	EATON - MOELLER
MPN / Reference	DC1-34014FB-A6SOE1
Catalog number	Y7-199440
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-36D061BB0D
Generated	2026-08-05

Product Overview

DC1-34014FB-A6SOE1

Eaton DC1 Variable frequency drive, 400 V AC, 3-phase, 14 A, 5.5 kW, IP66/NEMA 4X, Radio interference suppression filter, Brake chopper, 7-digital display assembly, Local controls, Additional PCB protection, UV resistant, FS3

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-10\%) - 480 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 14 \text{ A}$, Note: Rated operational current at an operating frequency of 6 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For normal internally and externally ventilated four-pole three-phase asynchronous motors with 1500 rpm at 50 Hz and 1800 rpm at 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 5.5 \text{ kW}$, 150 % Overload: $I_M = 11.3 \text{ A}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 10 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 14 \text{ A}$, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Radio interference suppression filter, Brake chopper, 7-digital display assem...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Power XL Frequency Converters
--------------	---

Additional Product Information

General specifications

Product Name Eaton DC1 Variable frequency drive

Catalog Number 199440

Model Code DC1-34014FB-A6SOE1

EAN 4015081978298

Product Length/Depth 238 mm

Product Height 310 mm

Product Width 210.5 mm

Product Weight 7 kg

Certifications UL 508C

Certified by UL for use in Canada

UkrSEPRO

UL

IEC/EN61800-5

UL report applies to both US and Canada

CSA-C22.2 No. 14

UL File No.: E172143

CUL

IEC/EN 61800-2

CE marking

IEC/EN 61800-5-1

EAC

UL Listed

IEC/EN 61800-3

RoHS, ISO 9001

CE

RCM

UL Category Control No.: NMMS, NMMS7

Catalog Notes Environmental class: 3C3, 3S3

Overload cycle for 60 s every 600 s

For normal internally and externally ventilated four-pole three-phase asynchronous motors with 1500 rpm at 50 Hz and 1800 rpm at 60 Hz

Features & Functions

Features Parameterization: Fieldbus

Parameterization: drivesConnect mobile (App)

Parameterization: drivesConnect

Parameterization: Keypad

Fitted with: PC connection

UV resistance

Internal DC link

Brake chopper

Control unit

Radio interference suppression filter

Additional PCB protection

Local controls

IGBT inverter

7-digital display assembly

Breaking resistance

Functions 4-quadrant operation possible

General information

Cable length 100 m, screened, maximum permissible cable length
200 m, screened, with motor choke, maximum permissible cable length
C2 <= 5 m, maximum motor cable length
C3 <= 25 m, maximum motor cable length
300 m, unscreened, with motor choke, maximum permissible, Motor feeder
150 m, unscreened, maximum permis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-34014FB-A6SOE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.