

INDUSTRIAL COMPONENT DATA

DC1-34039FB-A20CE1 185781 Y7-185781 EATON ELECTRIC

Variable frequency drive, 400 V AC, 3-phase, 39 A, 18.5 k..

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-34039FB-A20CE1



Manufacturer	EATON - MOELLER
MPN / Reference	DC1-34039FB-A20CE1
Catalog number	Y7-185781
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-AE14A0215A
Generated	2026-08-06

Product Overview

Variable frequency drive, 400 V AC, 3-phase, 39 A, 18.5 kW, IP20/NEMA 0, Radio interference suppression filter, Brake chopper, FS4

DC1-34039FB-A20CE1

Eaton DC1 Variable frequency drive, 400 V AC, 3-phase, 39 A, 18.5 kW, IP20/NEMA 0, Radio interference suppression filter, Brake chopper, FS4 DC1-34039FB-A20CE1

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-10\%) - 480 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 39 \text{ A}$, Note: Rated operational current at an operating frequency of 16 kHz and an ambient air temperature of $+50^\circ\text{C}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 18.5 \text{ kW}$, 150 % Overload: $I_M = 39 \text{ A}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 25 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 39 \text{ A}$, Degree of Protection: IP20/NEMA 0, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Radio interf...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Power XL Frequency Converters
--------------	---

Additional Product Information

General specifications

Product Name Eaton DC1 Variable frequency drive Catalog Number 185781 Model Code DC1-34039FB-A20CE1 EAN 4015081812806 Product Length/Depth 211 mm Product Height 418.5 mm Product Width 173 mm Product Weight 8.4 kg

Certifications UL Category Control No.: NMMS, NMMS7

IEC/EN 61800-3

Safety requirements: IEC/EN 61800-5-1

EAC

UL 508C

RCM

IEC/EN61800-3

UL

Certified by UL for use in Canada

CSA-C22.2 No. 14

RoHS, ISO 9001

UkrSEPRO

IEC/EN61800-5

CUL

CE

UL report applies to both US and Canada

Specification for general requirements: IEC/EN 61800-2

UL File No.: E172143 Catalog Notes Features & Functions

Features Parameterization: drivesConnect

Parameterization: drivesConnect mobile (App)

Parameterization: Fieldbus

Parameterization: Keypad Fitted with: IGBT inverter

Control unit

Brake chopper

Internal DC link

PC connection

Breaking resistance

7-digital display assembly

Radio interference suppression filter

Additional PCB protection Functions 4-quadrant operation possible General

Cable length 300 m, unscreened, with motor choke, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible, Motor feeder

150 m, unscreened, maximum permissible, Motor feeder

C3 <= 25 m, Radio interference level, maximum motor cable length

100 m, screened, maximum permissible, Motor feeder

C2 <= 5 m, Radio interference level, maximum motor cable length Communication interface CANopen®, built in

SmartWire-DT, optional

OP-Bus (RS485), built in

Modbus RTU, built in....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-34039FB-A20CE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.