

## INDUSTRIAL COMPONENT DATA

**DC1-344D1FB-A6SCE1 185751 EATON ELECTRIC Variable frequency drive, 400 V AC, 3-phase, 4.1 A, 1.5 kW, IP66/NE..**

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-344D1FB-A6SCE1



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | DC1-344D1FB-A6SCE1                 |
| Catalog number  | 185751                             |
| Category        | Frequency converter less than 1 kV |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-7E69762824                      |
| Generated       | 2026-08-05                         |

**Product Overview**

Variable frequency drive, 400 V AC, 3-phase, 4.1 A, 1.5 kW, IP66/NEMA 4X, Radio interference suppression filter, Brake chopper, Local controls, FS2

Frequency Converter. Ent: 3 x 400 V. Salt: 3 x 400 V. 4.1 A. 1.5 kW. V/f, SLV. EMC filter. Braking transistor. IP66

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: Ue = 400 V AC, 3-phase, 480 V AC, 3-phase, Output voltage with Ve: U2 = 400 V AC, 3-phase, 480 V AC, 3-phase, Mains voltage (50/60Hz): ULN = 380 (-10%) - 480 (+10%) V, Rated operational current At 150% overload: Ie = 4.1 A, Note: Rated operational current at a switching frequency of 16 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz , Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: P = 1.5 kW, 150 % Overload: IM = 3.6 A, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: P = 2 HP, Assigned motor rating 150 % Overload: IM = 3.4 A, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Radio interference suppression filter, Brake chopper, 7-d...

## STRUCTURED PRODUCT DATA

**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | EATON - MOELLER > Power XL Frequency Converters |
|--------------|-------------------------------------------------|

**Additional Product Information**

Variable frequency drive, 400 V AC, 3-phase, 4.1 A, 1.5 kW, IP66/NEMA 4X, Radio interference suppression filter, Brake chopper, Local controls, FS2Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: Ue = 400 V AC, 3-phase, 480 V AC, 3-phase, Output voltage with Ve: U2 = 400 V AC, 3-phase, 480 V AC, 3-phase, Mains

voltage (50/60Hz): ULN = 380 (-10%) - 480 (+10%) V, Rated operational current At 150% overload:  $I_e = 4.1$  A, Note: Rated operational current at a switching frequency of 16 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload:  $P = 1.5$  kW, 150 % Overload:  $I_M = 3.6$  A, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload:  $P = 2$  HP, Assigned motor rating 150 % Overload:  $I_M = 3.4$  A, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Radio interference suppression filter, Brake chopper, 7-digital display assembly, Local controls, Frame size: FS2, Standards: Specification for general requirements: IEC/EN 61800-2, EMC requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1 Delivery program

This....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-344D1FB-A6SCE1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.