

INDUSTRIAL COMPONENT DATA

DC1-345D8FB-A6SOE1 199436 Y7-199436 EATON ELECTRIC DC1-345D8FB-A6SOE1

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-345D8FB-A6SOE1



Manufacturer	EATON - MOELLER
MPN / Reference	DC1-345D8FB-A6SOE1
Catalog number	Y7-199436
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-3A69BB3594
Generated	2026-08-05

Product Overview

DC1-345D8FB-A6SOE1

Eaton DC1 Variable frequency drive, 400 V AC, 3-phase, 5.8 A, 2.2 kW, IP66/NEMA 4X, Radio interference suppression filter, Brake chopper, 7-digital display assembly, Local controls, Additional PCB protection, UV resistant, FS2 Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-10\%) - 480 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 5.8 \text{ A}$, Note: Rated operational current at an operating frequency of 6 kHz and an ambient air temperature of $+40^\circ \text{C}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For normal internally and externally ventilated four-pole three-phase asynchronous motors with 1500 rpm at 50 Hz and 1800 rpm at 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 2.2 \text{ kW}$, 150 % Overload: $I_M = 5 \text{ A}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 3 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 4.8 \text{ A}$, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Radio interference suppression filter, Brake chopper, 7-digital display assemb...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Power XL Frequency Converters
--------------	---

Additional Product Information

General specifications

Product Name Eaton DC1 Variable frequency drive Catalog Number 199436 Model Code DC1-345D8FB-A6SOE1 EAN 4015081978250 Product Length/Depth 182 mm Product Height 257 mm Product Width 188 mm Product Weight 3.5 kg

Certifications UL

IEC/EN 61800-5-1

UL Category Control No.: NMMS, NMMS7

RCM

IEC/EN 61800-3

UL File No.: E172143

UkrSEPRO

IEC/EN61800-5

UL 508C

Certified by UL for use in Canada

UL report applies to both US and Canada

CE marking

IEC/EN 61800-2

CSA-C22.2 No. 14

UL Listed

EAC

CUL

CE

RoHS, ISO 9001 Catalog Notes Features & Functions

Features Parameterization: drivesConnect mobile (App)

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: drivesConnect Fitted with: Brake chopper

7-digital display assembly

Local controls

PC connection

Radio interference suppression filter

Control unit

Additional PCB protection

Breaking resistance

Internal DC link

IGBT inverter

UV resistance Functions 4-quadrant operation possible General

Cable length 100 m, screened, maximum permissible cable length

150 m, unscreened, maximum permissible cable length

300 m, unscreened, with motor choke, maximum permissible, Motor feeder

200 m, screened, with motor choke, maximum permissible cable length

C3 ≤ 25 m, maximum motor cable length

C2 ≤ 5 m, maximum motor cable length Communication interface SmartWire-DT, optional

CANopen®, built in

OP-Bus (RS485), built in

Modbus RTU, built in Connection to SmartWire-DT No Degree of protection IP66

NEMA 4X Electromagnetic co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-345D8FB-A6SOE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.