

INDUSTRIAL COMPONENT DATA

DC1-S17D0NN-A66OE1 199383 EATON ELECTRIC Variable frequency drive, 115 V AC, single-phase, 7 A, 0.37 kW, IP66..

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-S17D0NN-A66OE1



Manufacturer	EATON - MOELLER
MPN / Reference	DC1-S17D0NN-A66OE1
Catalog number	199383
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-F3873C0888
Generated	2026-08-03

Product Overview

Variable frequency drive, 115 V AC, single-phase, 7 A, 0.37 kW, IP66/NEMA 4X, 7-digit display assembly, Additional PCB protection, UV resistant, FS1

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 115$ V AC, single-phase, Output voltage with V_e : $U_2 = 115$ V AC, single-phase, Mains voltage (50/60Hz): $U_{LN} = 110 (-10\%) - 115 (+10\%)$ V, Rated operational current At 150% overload: $I_e = 7$ A, Note: Rated operational current at an operating frequency of 6 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50/60 Hz without additional start capacitor, Overload cycle for 60 s every 600 s, at 115 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 0.37$ kW, 150 % Overload: $I_M = 7$ A, Assigned motor rating Note: at 110 - 120 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 0.5$ HP, Assigned motor rating 150 % Overload: $I_M = 5.8$ A, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: 7-digit display assembly, Additional PCB protection, UV resistant, Frame size: FS1, Standards: General requirements: IEC/EN 61800-2, EMV requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Power XL Frequency Converters
--------------	---

Additional Product Information

Variable frequency drive, 115 V AC, single-phase, 7 A, 0.37 kW, IP66/NEMA 4X, 7-digit display assembly, Additional PCB protection, UV resistant, FS1Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 115$ V AC, single-phase, Output voltage with V_e : $U_2 = 115$ V AC, single-phase, Mains voltage (50/60Hz): $U_{LN} = 110$

(-10%) - 115 (+10%) V, Rated operational current At 150% overload: $I_e = 7 \text{ A}$, Note: Rated operational current at an operating frequency of 6 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50/60 Hz without additional start capacitor, Overload cycle for 60 s every 600 s, at 115 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 0.37 \text{ kW}$, 150 % Overload: $I_M = 7 \text{ A}$, Assigned motor rating Note: at 110 - 120 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 0.5 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 5.8 \text{ A}$, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: 7-digital display assembly, Additional PCB protection, UV resistant, Frame size: FS1, Standards: General requirements: IEC/EN 61800-2, EMV requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1 Delivery program
Product range Variable frequency drives Part group reference (e.g. DIL) DC1 Rated operational voltage $[U_e]$ 115 V AC,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-S17D0NN-A66OE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.