

## INDUSTRIAL COMPONENT DATA

# DC1-S17D0NN-A6SCE1 186075 EATON ELECTRIC Variable frequency drives, 1-/single-phase 115 V, 7.0 A, 0.37 kW

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-S17D0NN-A6SCE1



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | DC1-S17D0NN-A6SCE1                 |
| Catalog number  | 186075                             |
| Category        | Frequency converter less than 1 kV |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-D7C9E82DA4                      |
| Generated       | 2026-08-03                         |

## Product Overview

Variable frequency drives, 1-/single-phase 115 V, 7.0 A, 0.37 kW

Frequency Converter. Ent: 1 x 115 V. Salt: 1 x 115 V. 7.0 A. 0.37 kW. V/f, SLV. IP66

Variable frequency drive, 115 V AC, single-phase, 7 A, 0.37 kW, IP66/NEMA 4X, Local controls, FS1

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage:  $U_e = 115 \text{ V AC}$ , single-phase, Output voltage with  $V_e$ :  $U_2 = 115 \text{ V AC}$ , single-phase, Mains voltage (50/60Hz):  $U_{LN} = 110 (-10\%) - 115 (+10\%) \text{ V}$ , Rated operational current At 150% overload:  $I_e = 7 \text{ A}$ , Note: Rated operational current at a switching frequency of 16 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50/60 Hz without additional start capacitor, Overload cycle for 60 s every 600 s, at 115 V, 50 Hz, Assigned motor rating 150 % Overload:  $P = 0.37 \text{ kW}$ , 150 % Overload:  $I_M = 7 \text{ A}$ , Assigned motor rating Note: at 110 - 120 V, 60 Hz, Assigned motor rating 150 % Overload:  $P = 0.5 \text{ HP}$ , Assigned motor rating 150 % Overload:  $I_M = 5.8 \text{ A}$ , Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: 7-digital display assembly, Local controls, Frame size: FS1, Standards: Specification for general requirements: IEC/EN 61800-2, EMC requ...

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | EATON - MOELLER > Power XL Frequency Converters |
|--------------|-------------------------------------------------|

## Additional Product Information

Variable frequency drive, 115 V AC, single-phase, 7 A, 0.37 kW, IP66/NEMA 4X, Local controls, FS1Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage:  $U_e = 115 \text{ V AC}$ , single-phase, Output voltage with  $V_e$ :  $U_2 = 115 \text{ V AC}$ , single-phase, Mains voltage (50/60Hz):  $U_{LN} = 110 (-10\%) - 115 (+10\%) \text{ V}$ , Rated operational current At

150% overload:  $I_e = 7 \text{ A}$ , Note: Rated operational current at a switching frequency of 16 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50/60 Hz without additional start capacitor, Overload cycle for 60 s every 600 s, at 115 V, 50 Hz, Assigned motor rating 150 % Overload:  $P = 0.37 \text{ kW}$ , 150 % Overload:  $I_M = 7 \text{ A}$ , Assigned motor rating Note: at 110 - 120 V, 60 Hz, Assigned motor rating 150 % Overload:  $P = 0.5 \text{ HP}$ , Assigned motor rating 150 % Overload:  $I_M = 5.8 \text{ A}$ , Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: 7-digital display assembly, Local controls, Frame size: FS1, Standards: Specification for general requirements: IEC/EN 61800-2, EMC requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1 Delivery program

This item is only available until 04/30/2021, after which it will be replaced with the following item: 199384, DC1-S17D0NN-A6SOE1 Product range Variable frequency drives Part....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-S17D0NN-A6SCE1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.