

INDUSTRIAL COMPONENT DATA

DC1-S27D0FN-A6SCE1 186093 EATON ELECTRIC Variable frequency drives, 1-/single-phase 230 V, 7.0 A, 0.75 kW, E..

Brand: EATON - MOELLER | Manufacturer Part Number: DC1-S27D0FN-A6SCE1



Manufacturer	EATON - MOELLER
MPN / Reference	DC1-S27D0FN-A6SCE1
Catalog number	186093
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-17D591679A
Generated	2026-08-05

Product Overview

Variable frequency drives, 1-/single-phase 230 V, 7.0 A, 0.75 kW, EMC Filters

Frequency Converter. Ent: 1 x 230 V. Salt: 1 x 230 V. 7.0 A. 0.75 kW. V/f, SLV. EMC filter. IP66

Variable frequency drive, 230 V AC, 1-phase, 7 A, 0.75 kW, IP66/NEMA 4X, Radio interference suppression filter, Local controls, FS1

Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 230$ V AC, 1-phase, 240 V AC, single-phase, Output voltage with V_e : $U_2 = 230$ V AC, single-phase, 240 V AC, single-phase, Mains voltage (50/60Hz): $U_{LN} = 200$ (-10%) - 240 (+10%) V, Rated operational current At 150% overload: $I_e = 7$ A, Note: Rated operational current at a switching frequency of 16 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50/60 Hz without additional start capacitor, Overload cycle for 60 s every 600 s, at 230 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 0.75$ kW, 150 % Overload: $I_M = 7$ A, Assigned motor rating Note: at 220 - 240 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 1$ HP, Assigned motor rating 150 % Overload: $I_M = 6.8$ A, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Radio interference suppression filter...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

Variable frequency drive, 230 V AC, 1-phase, 7 A, 0.75 kW, IP66/NEMA 4X, Radio interference suppression filter, Local controls, FS1
Variable frequency drive, Part group reference (e.g. DIL): DC1, Rated operational voltage: $U_e = 230$ V AC,

1-phase, 240 V AC, single-phase, Output voltage with V_e : $U_2 = 230$ V AC, single-phase, 240 V AC, single-phase, Mains voltage (50/60Hz): $U_{LN} = 200$ (-10%) - 240 (+10%) V, Rated operational current At 150% overload: $I_e = 7$ A, Note: Rated operational current at a switching frequency of 16 kHz and an ambient air temperature of +40 °C, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50/60 Hz without additional start capacitor, Overload cycle for 60 s every 600 s, at 230 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 0.75$ kW, 150 % Overload: $I_M = 7$ A, Assigned motor rating Note: at 220 - 240 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 1$ HP, Assigned motor rating 150 % Overload: $I_M = 6.8$ A, Degree of Protection: IP66/NEMA 4X, Interface/field bus (built-in): OP-Bus (RS485)/Modbus RTU, CANopen®, Fieldbus connection (optional): SmartWire-DT, Fitted with: Radio interference suppression filter, 7-digital display assembly, Local controls, Frame size: FS1, Standards: Specification for general requirements: IEC/EN 61800-2, EMC requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1 Delivery program

This item is only available until 04/30/2021, after which....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DC1-S27D0FN-A6SCE1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.