

INDUSTRIAL COMPONENT DATA

DDC-250/2-SK 6098941 Y8-6098941 EATON ELECTRIC DC switch disconnector, 250 A, 2 pole, 2 N/O, 2 N/C, Without ..

Brand: EATON - MOELLER | Manufacturer Part Number: DDC-250/2-SK



Manufacturer	EATON - MOELLER
MPN / Reference	DDC-250/2-SK
Catalog number	Y8-6098941
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-304998C208
Generated	2026-08-03

Product Overview

DC switch disconnector, 250 A, 2 pole, 2 N/O, 2 N/C, Without rotary handle and drive shaft, rear mounting

DDC-250/2-SK

DC switch disconnector, Product range: DC switch-disconnector, Main switch, maintenance switch, Part group reference: DDC, Stop Function: optional, Without rotary handle and drive shaft, Information about equipment supplied: auxiliary contact fitted by user., 2 pole, Degree of Protection: IP20, Design: rear mounting, Rated uninterrupted current: $I_u = 250\text{ A}$, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DDC Insulated enclosure Catalog Number 6098941 Model Code DDC-250/2-SK EAN

8711426422308 Product Length/Depth 240 mm Product Height 129 mm Product Width 127 mm Product Weight 5 kg

Certifications RoHS

IEC/EN 60947-3

IEC/EN 60947

IEC/EN 60204

VDE 0660

CE Features & Functions

Actuator color Other Actuator type Other Features Version as maintenance-/service switch

Version as main switch Functions Optional Stop Function Number of poles Two-pole General

Accessories Auxiliary contact fitted by user. Degree of protection NEMA Other Degree of protection (front side) IP20

Lifespan, mechanical 10,000 Operations Mounting method Rear mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 12000 V Suitable for Ground mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities

Terminal capacity 1 x 240 mm², solid

1 x (25 x 6) mm², Flat conductor connection with busbars Screw size M10, Terminal screw Tightening torque 20 Nm, Screw terminals Electrical rating

Rated operational current (Ie) at DC-21B, 1000 V 250 A Rated operational current (Ie) at DC-21B, 480 V 250 A Rated operational current (Ie) at DC-21B, 600 V 250 A Rated operational power at AC-23A, 400 V, 50 Hz 0 kW Rated uninterrupted current (Iu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DDC-250/2-SK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.