

INDUSTRIAL COMPONENT DATA

DDC-400/2/M4/P-G 6098945 Y8-6098945 EATON ELECTRIC DC switch disconnecter, 400 A, 2 pole, 2 N/O, 2 N/C, with..

Brand: EATON - MOELLER | Manufacturer Part Number: DDC-400/2/M4/P-G



Manufacturer	EATON - MOELLER
MPN / Reference	DDC-400/2/M4/P-G
Catalog number	Y8-6098945
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-1B889E972A
Generated	2026-08-05

Product Overview

DC switch disconnecter, 400 A, 2 pole, 2 N/O, 2 N/C, with grey knob, rear mounting

DDC-400/2/M4/P-G

DC switch disconnecter, Product range: DC switch-disconnector, Main switch, maintenance switch, Part group reference: DDC, with grey knob, Notes: With metal shaft for a control panel depth of 400 mm, Information about equipment supplied: auxiliary contact fitted by user., 2 pole, Degree of Protection: IP20, Design: rear mounting, Rated uninterrupted current: $I_u = 400$ A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

DC switch disconnecter, 400 A, 2 pole, 2 N/O, 2 N/C, with grey knob, rear mountingDC switch disconnecter, Product range: DC switch-disconnector, Main switch, maintenance switch, Part group reference: DDC, with grey knob, Notes: With metal shaft for a control panel depth of 400 mm, Information about equipment supplied: auxiliary contact fitted by user., 2 pole, Degree of Protection: IP20, Design: rear mounting, Rated uninterrupted current: $I_u = 400$ A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

General specificationsProduct nameEaton DDC Insulated enclosurePart

no.DDC-400/2/M4/P-GEAN8711426744073Product Length/Depth240 millimetreProduct height129 millimetreProduct width127 millimetreProduct weight5 kilogramCertificationsVDE 0660

IEC/EN 60204

IEC/EN 60947

CE

IEC/EN 60947-3

RoHSProduct TradenameDDCProduct TypeInsulated enclosureProduct Sub TypeNoneCatalog NotesRated Short-time
Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsActuator colorGrayActuator typeLong turning
handleFeaturesVersion as main switch

Version as maintenance-/service switchFitted with:Metal shaft for a control panel depth of 400 mm

Gray knobFunctionsInterlockableNumber of polesTwo-poleGeneral informationAccessoriesAuxiliary contact fitted by
user.Degree of protectionNEMA OtherDegree of protection (front side)IP20Lifespan, mechanical10,000

OperationsMounting methodRear mountingMounting positionAs requiredOvervoltage categoryIIIPollution degr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DDC-400/2/M4/P-G with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.