

INDUSTRIAL COMPONENT DATA

DDC-63/2 6098920 Y8-6098920 EATON ELECTRIC DC switch disconnecter, 63 A, 2 pole, 1 N/O, 1 N/C, with grey kno..

Brand: EATON - MOELLER | Manufacturer Part Number: DDC-63/2



Manufacturer	EATON - MOELLER
MPN / Reference	DDC-63/2
Catalog number	Y8-6098920
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-27203CDBD8
Generated	2026-08-04

Product Overview

DC switch disconnecter, 63 A, 2 pole, 1 N/O, 1 N/C, with grey knob, service distribution board mounting
DDC-63/2

DC switch disconnecter, Product range: DC switch-disconnector, Main switch, maintenance switch, Part group reference: DDC, with grey knob, Information about equipment supplied: auxiliary contact fitted by user., 2 pole, Degree of Protection: Front IP65, Design: service distribution board mounting, Rated uninterrupted current: $I_u = 63$ A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > DUMECO Switch-Disconnectors
--------------	---

Additional Product Information

General specifications

Product Name Eaton DDC Insulated enclosure Catalog Number 6098920 Model Code DDC-63/2 EAN 8711426317727
Product Length/Depth 132 mm Product Height 97 mm Product Width 90 mm Product Weight 1.5 kg Certifications IEC/EN 60947
VDE 0660
RoHS
IEC/EN 60204
IEC/EN 60947-3

CE Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second Features & Functions
Actuator color Gray Actuator type Long turning handle Features Version as main switch

Version as maintenance-/service switch Fitted with: Gray knob Functions Interlockable Number of poles Two-pole General Accessories Auxiliary contact fitted by user. Degree of protection NEMA Other Degree of protection (front side) IP20 Lifespan, mechanical 10,000 Operations Mounting method Service distribution board mounting Mounting position As required Overvoltage category III Pollution degree 3 Product Category Rated impulse withstand voltage (Uimp) 8000 V Suitable for Ground mounting Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -30 °C Ambient storage temperature - max 80 °C Terminal capacities Terminal capacity 6 - 35 mm², solid 6 - 25 mm², flexible Stripping length (main cable) 15 mm Tightening torque 3 Nm, Screw terminals Electrical rating Rated operational current (Ie) at DC-21B, 1000 V 63 A Rated operational current (Ie) at DC-21B, 480 V 63 A Rated operational current (Ie) at DC-21B, 600 V 63 A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DDC-63/2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.