

INDUSTRIAL COMPONENT DATA

DDC-630/2-SK 6098947 Y8-6098947 EATON ELECTRIC DC switch disconnecter, 630 A, 2 pole, 2 N/O, 2 N/C, Without ..

Brand: EATON - MOELLER | Manufacturer Part Number: DDC-630/2-SK



Manufacturer	EATON - MOELLER
MPN / Reference	DDC-630/2-SK
Catalog number	Y8-6098947
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-598A7068B0
Generated	2026-08-05

Product Overview

DC switch disconnecter, 630 A, 2 pole, 2 N/O, 2 N/C, Without rotary handle and drive shaft, rear mounting
DDC-630/2-SK

DC switch disconnecter, Product range: DC switch-disconnector, Main switch, maintenance switch, Part group reference: DDC, Stop Function: optional, Without rotary handle and drive shaft, Information about equipment supplied: auxiliary contact fitted by user., 2 pole, Degree of Protection: IP20, Design: rear mounting, Rated uninterrupted current: $I_u = 630$ A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > DUMECO Switch-Disconnectors

Additional Product Information

DC switch disconnecter, 630 A, 2 pole, 2 N/O, 2 N/C, Without rotary handle and drive shaft, rear mounting
DC switch disconnecter, Product range: DC switch-disconnector, Main switch, maintenance switch, Part group reference: DDC, Stop Function: optional, Without rotary handle and drive shaft, Information about equipment supplied: auxiliary contact fitted by user., 2 pole, Degree of Protection: IP20, Design: rear mounting, Rated uninterrupted current: $I_u = 630$ A, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

General specifications
Product name Eaton DDC Insulated enclosure
Part no. DDC-630/2-SKEAN8711426102316
Product Length/Depth 240 millimetre
Product height 129 millimetre
Product width 127 millimetre
Product weight 5 kilogram
Certifications VDE 0660
IEC/EN 60947-3
IEC/EN 60204

CE

RoHS

IEC/EN 60947Product TradenameDDCProduct TypeInsulated enclosureProduct Sub TypeNoneCatalog NotesRated

Short-time Withstand Current (Icw) for a time of 1 second

Without rotary handle and drive shaftFeatures & FunctionsActuator colorOtherActuator typeOtherFeaturesVersion as main switch

Version as maintenance-/service switchFunctionsOptional Stop FunctionNumber of polesTwo-poleGeneral informationAccessoriesAuxiliary contact fitted by user.Degree of protectionNEMA OtherDegree of protection (front side)IP20Lifespan, mechanical10,000 OperationsMounting methodRear mountingMounting positionAs requiredOvervoltage categoryIIIPollution degree3Product CategoryDC switch-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DDC-630/2-SK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.